

SURVEY &

\$7.00 REMONUMENTATION

\$2.00

SEP 18 1995

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

Kent

COMMISSION
(County)

Located in:

Corner Code #

1. Public Land Survey T 5N R 12W A-9
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

I, Randy Kolehouse, in a field survey on March 13 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

| | | | | |
|-----|------|----------------|--------------------|--------------------------------|
| A-9 | 1817 | G.L.O. Notes | L. Lyon | Set Post |
| | | Wit. Map | K.C. Surveyor | Leaded Stone |
| | 1953 | Wit. Map | K.C. Surveyor | Leaded Stone |
| | 1981 | L.C.R.C. #2305 | Nederveld & Assoc. | Fnd. 6" Nail/Set K.C. Monument |
| | 1988 | L.C.R.C. #4631 | Olson, Meyers, May | K.C. Monument |

P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/25/95

CHAIRMAN Randy Kolehouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Associates on 9/3/81 and was recorded per L.C.R.C. #2305.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-9 Found a standard Kent County Monument on the Town line at the C/L intersection of Kenowa Avenue running N-S and 92nd Street running East per L.C.R.C.'s #2305 and #4631 as set by Nederveld Associates in place of a 1/4" x 6" nail they found which checks the location of the leaded stone shown in K.C. Surveyor's records.

L.C.R.C. #2305

L.C.R.C. #4631

SE corner Sec. 24, T5N, R13W 3/4" rd. Iron S0°W 75.90'
Nail & K.D. Remon. tag N side P. pole S45°E 160.42'
NE cor. brick porch S35°W 163.40'

SE cor Sec 24, T5N, R13W, 3/4" rd Iron S 0 W 75.90'
Nail & K.C. Remon tag E sde 22" Walnut S 20 W 97.77'
Nail & K.C. Remon tag N sde P pole S 45 E 160.42'
NE cor brick porch S 35 W 163.40'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-9 Standard Kent County Monument on the Town Line

Nail & K.C. remon. tag in E side 20" Walnut S 20° W 97.77'
NE corner brick porch S 35° W 163.40'
Nail & K.C. remon. tag in N side P. pole S 45° E 160.42'
SE corner Sec 24, T5N, R13W, 3/4" road iron South 75.90'

Signed by Randy J. Kolehouse

Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854