

SURVEY &  
REMONUMENTATION

APR 27 1995

COMMISSION

For corners in

Kent

(County)

Located In:

Corner Code =#

1. Public Land Survey

T 5N R 12W

B-2

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

94 DEC 28 PM 2:15

REG. OF DEEDS

7917

Register of Deeds Stamp & File Number

I, Douglas W. Bonnema in a field survey on Nov. 11, 19 94,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

\*Since this is not a government corner, there is no G.L.O. information.

Williams & Works 1965 Set "T" iron at intersection of 1/4 lines.

MBT pole W-NW 108.82'

Exxel Engineering 1974 Fount "T" iron

SW cor. house NE 102.28'

PK nail in W sde P.Pole S-SW 88.93'

Fence post S-SW 26.22'

SW cor. garage fndn N-NE 96.38'

P.Pole E=NE 48.5'

PK nail in E sde P.Pole E-NE 48.97'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found "T" iron in Mon. Box.

Found PK nail in W sde P.Pole

S09°W 89.00'

Found PK nail in SE sde T. Pole

SE 48.95'

SW cor. garage fndn.

N-NE 96.38'

P.A. 345 1975 KENT COUNTY

PEER APPROVED 5/26/99

CHAIRMAN *[Signature]*

The selected location is accepted by me and is generally accepted by professional  
surveyors as the best available evidence of the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced "T" iron with 4"x12" Kent County Cast Iron Monument in Monument Box.

Nail & KC tag in W sde P.Pole

S09°W 89.00'

Nail & KC tag in S'y sde T.Pole

N78°W 133.83'

Nail & KC tag in SE sde T.Pole

N64°E 48.95'

SW cor. garage fndn.

N23°E 96.38'

SE cor. house fndn.

N56°E 125.73'

NW cor. house fndn.

S58°E 215.03'

C/L BT pavement

North 0.5'±

Signed by *Douglas W. Bonnema*

Date 12/14/94

Surveyor's Michigan License No. 12579

