

\$7.00 SEP 1 8 1995  
\$2.00 COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

- |                                       |                          |            |
|---------------------------------------|--------------------------|------------|
| 1. Public Land Survey                 | T <u>5N</u> R <u>12W</u> | <u>C-7</u> |
|                                       | T _____ R _____          | _____      |
|                                       | T _____ R _____          | _____      |
|                                       | T _____ R _____          | _____      |
| 2. Property Controlling<br>in Section | S _____ T _____ R _____  | _____      |
|                                       | S _____ T _____ R _____  | _____      |
| 3. Miscellaneous                      | S _____ T _____ R _____  | _____      |
| Property in Sec.                      | S _____ T _____ R _____  | _____      |

REG. OF DEEDS

*Handwritten signature*

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 AUG 28 AM 10:48

8570

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehose, in a field survey on March 14 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-7	1831	G.L.O. Notes	Mullett	Set Post	PEER APPROVED <u>5/25/95</u>
	1944	Wit. Map	K.C. Surveyor	2" Pipe	CHAIRMAN <i>Handwritten signature</i>
	1972	L.C.R.C. #198	Williams & Works	1/2" Iron in Monument Box	
	1976	L.C.R.C. #1003	Medema, Van Kooten & Assoc.	Iron in Monument Box	
	1981	L.C.R.C. #1569	Nederveld & Jonker	Fnd. 1/2" Iron in Mon. Box/Set K.C. Monument	
	1988	L.C.R.C. #4640	Olson, Meyers & May	K.C. Monument in Monument Box	

P.A. 345 1990 KENT COUNTY

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 1/5/81 and was recorded per L.C.R.C. #1569.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-7 Found standard Kent County Monument in a monument box at the C/L intersection of Wilson Avenue running N-S and 84th Street running E-W per L.C.R.C.'s #1569 and #4640 as set by Nederveld & Jonker in place of a 1/2" iron in monument box they found which checked L.C.R.C.'s #1003 and #198.

L.C.R.C. #1569

K.C.R.C. Remon. tag on NE side guy pole SE 51.2'  
K.C.R.C. Remon tag. on side P. & T. pole NW 64.70'  
"X" in curb radius SE 36.10'

L.C.R.C. #4640

K.C.R.C. Remon tag & nail on NE sde guy pole S 55 E 51.2'  
K.C.R.C. Remon tag & nail on sde P & T pole N 60 W 64.70'  
K.C.R.C. Remon tag & nail on top cor fence post N 50 E 76.14'  
"X" in curb radius S 40 E 36.10'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-7 Standard Kent County Monument in a Monument Box

Nail & K.C. remon. tag on NE side P. pole S 55° E 51.20'  
Nail & K.C. remon. tag on SW side P. pole N 60° W 65.02'  
Nail & K.C. remon. tag on top cor. fence post N 50° E 76.50'  
"X" in conc. curb radius S 40° E 36.20'  
"X" in conc. curb radius N 49° E 36.61'

Signed by *Handwritten signature of Randy J. Kolehose*  
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No. 25854

