COMMISSION			LAND CORNER Filing Require	1970	
For c	orners in		KENT COL	INTY REMONUMENTATION	, 8 8 <sub>0</sub>
	Kent (Co	unty)	Located in:	Corner Code #	ALCOUNT CENTER OF THE CONTROL OF THE
	(00				33
1. F	ublic Land	d Survey	T 5N R 12W	E-13	
			TR		
					10 CON 10
			TR	1	
	Property Con Section				8596 5 5
	r section Aiscellane	ous S	T R T B		
	roperty in		TR		Register of Deeds Stamp & File Number
				,	
4. L	ot No	, Recorde	d Plat		
5. F	rivate Cla	ims			A B C D E F G H I J K L
					2 6 5 3 - 2 - 1 -
					3
I.	Randv Kol	ehouse . in a	field survey on April	<u>11</u> 19 <u>95</u>	4 7 8 9 10 11 12
do he	reby certif	y that under requires	nents of P.A. 74 Michigar	P.A. of 1970, the corner po	pints 5
				ions and rules therefore as requ	
in the	current ma	anual of survey instruct	tions of the United States D	epartment of the interior, Burea corner points mentioned in line	au of
				n Board of Land Surveyors or	
				ented, re-monumented, recove	
found	as express				10 30 39 35 37 36 35
NOTE			all in the same town and	range, may be recorded	
	on thi	s certificate.			12 31 32 34 35 35
۸	Danaviati	an af aniainal magnin	·	d/or subsequent restoration:	
A.	Descripti	on or onginal monur	nent and accessories and	aror subsequent restoration.	P.A. 345 1990 KENT COUNTY
E-13	1817	G.L.O. Notes	L. Lyon	Set Post	PEER APPROVED 6/25/95
	N/A	Wit. Map	K.C. Surveyor	Long Stone	CHAIRMAN facy thefre
	N/A	Wit. Map	Kent County	1/2" Iron	CHAIRMAN / Lucy / MINA
	1981	L.C.R.C. #2304	Nederveld & Joni		n/Set K.C. Monument
	1986	L.C.R.C. #4426	Jonker		Mon. per Wit. L.C.R.C. #2304
	1988	L.C.R.C. #4614	J. Bueche	K.C. Monum	nent
			proved by the Kent Cour orded per L.C.R.C. #2304.	ity Remonumentation Peer C	Group and monumented by Nederveld &
B.	Descripti	on of corner evidenc	e found and/or method a	pplied in restoring or reesta	blishing corner:
E-13	108th Str	eet running E-W. Th	is point is on the Town lin		nning N-S and 1.0' North of the C/L of T4N, R12W, per L.C.R.C.'s #4426 and nothercked the K.C. Wit. Map.
		L.C.R.C. #4426	3	L.C.R.C. #4	614
		ag on NW side cor. fe ag on E side p & t pok		Top C/L M.B.T. Box #319	e P & T pole S 35 W 64.63' 8 S 15 E 47.01' N sde 12" tree S 80 W 88.03'
	The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.				
C.	Description of monument for corner and accessories established to perpetuate locating the position of the corner:				
E-13	Standard Kent County Monument				
	Nai Nai Nai Nai	& K.C. remon. tag or & K.C. remon. tag or & K.C. remon. tag or	NW side cor. fence post land in E side T. pole S 35° W 60 N side 12" Maple S 80° V in SE side 10" Maple S 60° NW side fence post N 48° E 47.01'	4.63 V 88.03' W 41.44'	RANDY J.  KOLEHOUSE  LAND SURVEYOR No. 25854
		Da. 10	Var/		Clause LANU Summer
Signe	d by	undy &	- server	Date	8/21/75
		<b>∕ €</b> ∕AR'	IH TECH		

25854

Surveyor's Michigan License No.