

\$7.00
\$2.00

SEP 13 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

G-2

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REG. OF DEEDS

8605

95 AUG 28 AM 10:51

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

Register of Deeds Stamp & File Number

I, Randy Kolehose, in a field survey on April 12 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-2	1831	G.L.O. Notes	Mullett	Set Post
	1949	Wit. Map	K.C. Surveyor	"X" on C/L Conc.
	1959	Wit. Map	K.C. Surveyor	Monument Box
	1971	L.C.R.C. #39	Williams & Works	Fnd. 3/4" Iron in Mon. Box
	1980	L.C.R.C. #1539	Exxel Engineering	Fnd. 3/4" Iron in Mon. Box/Set K.C. Monument
	1988	L.C.R.C. #4653	Olson, Meyers & May	Replaced Broken K.C. Mon. with New K.C. Mon.

P.A. 345 1990 KENT COUNTY
PEER APPROVED 5/25/95
CHAIRMAN Harry Hubert

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 12/16/80 and was recorded per L.C.R.C. #1539.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-2 Found standard Kent County Monument at C/L intersection of 64th Street running E-W and Byron Center Road running N-S. Per L.C.R.C.'s #1539 and #4653 as set by Exxel Engineering in place of a 3/4" iron in monument box they found which checks L.C.R.C. #39 and K.C. Surveyor's Wit. Map (1959) and reset by Olson, Meyers & May (L.C.R.C. #4653).

L.C.R.C. #1539

L.C.R.C. #4653

Nail & tag in N sde 20" Pear (3.5' above ground)

N75°W 139.85'

Nail & tag in S sde Triple 12" Aspen (4.5' above ground)

N46°W 178.82'

Capped EXXEL 1/2" re-rod S46°E 52.54'

Nail & tag in N sde 22" Pear (3.5' above ground)

N 75 W 139.85'

Nail & tag in S sde triple 14" Aspen (4.5' above ground)

N 46 W 178.82'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-2 Standard Kent County Monument

Nail & K.C. remon. tag on bt. spike W face M.B.T. pole N 27° E 102.07'

Nail & K.C. remon. tag on spike SW side P. pole N 32° W 74.99'

Nail & K.C. remon. tag on N side 24" Pear (3.5' above ground) N 75° W 139.85'

Nail & K.C. remon. tag on S side Triple 16" Aspen (4.5' above ground) N 46° W 178.92'

Signed by Randy J. Kolehose Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

