

# SURVEY & REMONUMENTATION

APR 27 1995

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

94 DEC 28 PM 2:15

For corners in

Kent

(County)

Located In:

Corner Code ##

1. Public Land Survey

T 5N R 12W

J-2

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REG. OF DEEDS

7916

Register of Deeds Stamp & File Number

I, Douglas W. Bonnema, in a field survey on Nov. 10, 19 94,  
do hereby certify that under requirements of P.A. 74; Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

### A. Description of original monument and accessories and/or subsequent restoration:

Since this is not a government corner, there is no G.L.O. information.

Williams & Works 1908 to 1957 Found and  
used large stone  
8" Cherry NE 42.75'  
20" Maple SE 37.6'  
Stone N 33'

Exxel Engineering 1977 Found 1/2" iron  
PK in W sde P.Pole N 39.92'  
PK in S sde P.Pole W-NW 154.83'

P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/26/94

CHAIRMAN Harry Huber

### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron at surface and large stone 14" below  
PK in W sde of old P.Pole North 39.94'  
PK in S sde of P.Pole W-NW 154.88'

We calculate the iron is 5.6'± West of the intersection of the 1/4 lines.

The selected location is accepted by me and is generally accepted by professional  
surveyors as the best available evidence of the position of the corner.

### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced 1/2" iron with 4" x 12" Kent County Cast Iron Mon.

K.C. tag & nail in S sde 30" Wild Cherry

KC tag & nail in W sde 15" Maple

KC tag in S sde P.Pole

KC tag in W sde new P.Pole

KC tag in SW sde T.Pole

SE cor of bricks on garage

C/L B.T. pavement

SW cor of house

N80°E 108.14'

N04°E 65.71'

N71°W 154.88'

N05°E 41.49'

S47°W 43.25'

N18°W 165.47'

South 1.8'

N18°E 109.55'

Signed by

Douglas W. Bonnema

Date

12/14/94

Surveyor's Michigan License No.

12579

