

LAND CORNER RECORDATION CERTIFICATE

Ear	corners in		Filing Requir	rement of Act 74, Mich. P.A. 1 DUNTY REMONUMENTATION	\ .	
FOLC			1 I I	i .		
_	Kent (Coun	ty)	Located in:	Corner Code #	9/6/8	
1.	Public Land S	Survey	T <u>5N</u> R <u>12W</u> T R T R	K-13		2007 2007 2007 2007 2007 2007 2007 2007
	Property Con in Section	_	T R T		8656	
	Miscellaneou Property in S		_ T R		Register of Deeds Stamp & F	ile Number
4.	Lot No	, Recorded	Plat	·		
5.	Private Claim	s			A B C D E F G	н I J K L
			- manual (1) - man		2 - 6 - 5 - 4 3	-3
	5					
do b				urch 4 19 95		-101112-
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points 5 mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required						
				Department of the interior, Burea		-1514
				he corner points mentioned in line		
				gan Board of Land Surveyors or I		-222324
			i, re-established, monu	mented, re-monumented, recove	red, ,	
	l as expressed				10 30 29 28	27 26 25-
NOT			I in the same town an	nd range, may be recorded	- 11	Ĩ ÎÎ.
	on this	certificate.			12 31 32 33	
A.	Description	of original monume	ent and accessories a	.nd/or subsequent restoration:		3 3 3 3
					P.A. 345 1900 KENT	COUNTY
K-13	1817	G.L.O. Notes	L. Lyon	Set Post	PEER APPROVED &	127/99
	1939	Wit. Map L.C.R.C. #1344	K.C. Surveyor	Leaded Stone	CHAIRMAN	Allert
	1980 1981	L. 1812	Exxel Engineerin Exxel Engineerin	- -	i. box	7
	1991	L.C.R.C. #6355	Chris Marschall	K.C. Monument	e/Set K.C. Monument	
		was originally appro and was recorded pe		y Remonumentation Peer Grou	and monumented by Exxel En	gineering
В.	Description	of corner evidence	found and/or method	applied in restoring or reestal	olishing corner:	
K-13 Found standard Kent County Monument at the C/L intersection of Clyde Park Avenue running N-S and 108th Street running E-W per L.C.R.C.'s #1812 and #6355 as set by Exxel Engineering in place of a leaded stone they found which checked K.C.R.C. Wit. 1939 and E.H. Christ notes (1902). This point is on the Town line and is 8.56' West of NW cor., Sec. 1, T5N R11W per K.C. Surveyor's records.						
-		L.C.R.C. #1812		L.C.R.C. #69	355	
	PK and KC	g in SE sde P. Pole N tag in S sde P. Pole I id in Mon. Box East 4	N82°W 186.94'	Nail & Tag SE Side P.P. N Nail & Tag S Side P.P. N NE Corner (brick) Hse 479 NW Corner (brick) Hse 47 3/4" Rod in Mon. Box East	78 W 186.94' 96 S 62 W 163.91' 95 S 60 E 195.59'	
		d location is accepte on of the original corr		lly accepted by professional sur	veyors as the best available evic	lence
C.	Description	of monument for co	rner and accessories	established to perpetuate loc	ating the position of the corner	
K-13	Standard Ke	ent County Monumen	t		nyakite of	MICHIGAR
C:	Nail & NE co NW co 3/4" ro		5 S 60° E 195.59'	186,94'	€ SURV	IOUSE
Signe	ed by	FARTH	TECH	Date	The Manne	1 + 2 4 5 2 3 2 7

25854

Surveyor's Michigan License No.