

SEP 18 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

L-11

2. Property Controlling
in Section

S

T

R

3. Miscellaneous
Property in Sec.

S

T

R

S

T

R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

REG. OF DEEDS

8662

Register of Deeds Stamp & File Number

95 AUG 28 AM 10:55

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

I, Randy Kolehouse, in a field survey on April 3 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-11	1831	G.L.O. Notes	Mullett	Set Post	P.A. 345 1990 KENT COUNTY
	1936	Wit. Map	K.C. Surveyor	Iron & Leaded Stone	PEER APPROVED 6/27/99
	1959	Wit. Map	K.C. Surveyor	Iron & Leaded Stone	CHAIRMAN <u>Harry Thube</u>
	1972	L.C.R.C. #749	Don Ratekin	Found 1" Iron in Mon. Box	
	1976	L.C.R.C. #985	Medema, Van Kooten & Assoc.	Found Mon. Box	
	1981	L.C.R.C. #1815	Exxel Engineering	Found 1" Iron in Mon. Box/Set K.C. Monument	
	1991	L.C.R.C. #6360	Chris Marschall	K.C. Monument	

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 3/26/81 and was recorded per L.C.R.C. #1815.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-11 Found standard Kent County Monument in the C/L of 100th Street running E-W per L.C.R.C.'s #985, #1815 and #6360 as set by Exxel Engineering in place of a 1" iron in monument box they found which checked L.C.R.C.'s #508, #749 and #985.

L.C.R.C. #1815

L.C.R.C. #6360

Nail & KC tag in E'ly sde 10" Maple N30°W 109.10'
Nail & KC tag in E'ly sde 12" Elm S3°E 49.50'

Nail & Tag E'ly sd. 16" Maple N 30° W 108.96'
Nail & Tag E'ly sd. 16" Elm S 3° E 49.42'
Nail & Tag NW sd. U.P. S 66° W 67.12'
Nail & Tag E. sd. U.P. N 26° W 47.14'
Nail & Tag NE sd. U.P. S 64° E 69.69'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-11 Standard Kent County Monument

Nail & K.C. remon. tag on E'ly side. 16" Maple N 30° W 108.96'
Nail & K.C. remon. tag on E'ly side 16" Elm S 03° E 49.42'
Nail & K.C. remon. tag on NW side Utl. pole S 66° W 67.12'
Nail & K.C. remon. tag on E. side Utl. pole N 26° W 47.14'
Nail & K.C. remon. tag on NE side Utl. pole S 64° E 69.69'

Signed by

Randy J. Kolehouse
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No.

25854

