## COMMISSION LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970				
For	corners in		OUNTY REMONUMENTATION	, <b>9</b>
· —	Kent (County)	Located in:	Corner Code #	-
	, ,,			で と い の
1.	Public Land Survey	T_5N_R_12W	L-12	900 - 503
	• •	TR_		**************************************
		TR		ライン 10 温温
2.	Property Controlling	T R S T R	V00.)	9: 0
	in Section	STR		8744 8
•	Miscellaneous	STR		
	Property in Sec.	S T P		Register of Deeds Stamp & File Number
	Lot No, Re			<del>_</del>
) <b>3.</b>	Private Claims			A B C D E F G H I J K L
				2 6 6 5 6 7 1 2 7 1 7
· •	•			3
	Randy Kolehouse	, in a field survey on Ar	<u>ril 6</u> 19 <u>95</u> ,	4 7 - 4 9 - 10 - 11 - 12 -
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points smentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required				
in the	current manual of survey i	instructions of the United States	Department of the interior, Bureau of	17-18-15-15-13-13-
Land	Management or by a decre	e of a Court of Law and/or that	he corner points mentioned in lines 3,	, 7
Decr	ee of a Court of Law; es	tablished, re-established moni	gan Board of Land Surveyors or by a imented, re-monumented, recovered,	5 - 19 - 20 - 21 - 22 - 23 - 24
found	as expressed below:			
NOT		ners, all in the same town a	nd range, may be recorded	10 30 29 28 27 25
	on this certificate.			"
Α.	Description of original	monument and accessories	.nd/or subsequent restoration:	12 31 32 33 34 35 36
•		nonument and accessories a	maror subsequent restoration:	19 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
L-12	This corner was not original	inally set by the G.L.O.	•	
	,			
	?? West County 1981 L.C.R.C. #1/	1	Iron	
	1981 L.C.R.C. #1	836 Exxel Engineer	ing Set Capped Re-	rod at Int. of 1/4 Lines
В.	Description of corner ev	vidence found and/or method	annied in restoring or reestablish	ing corner
L-12	Description of corner evidence found and/or method applied in restoring or reestablishing corner:			
L-12	Found capped iron set by Exxel Engineering at the intersection of 1/4 lines per L.C.R.C. #1836. Capped re-rod is at the intersection of 1/4 lines. Accepted capped re-rod as Center Section.			
	L.C.R.C.	#1836	· :	
	Nail in SE sde 14" W. Ch	erry S 22° W 5.54'	P.A. 3	45 1990 KENT COUNTY
	Nail in N sde 26" W. Che	rry S 58° W 3.41	PEER	APPROVED 8/24/95
	Nail in NE sde 12" Ash N	54° W 25.39'	CHAIR	MAN Fare Delho
		i .	1	- James
			1	,
	The selected location is a	accepted by me and is general	y accepted by professional surveyo	ors as the best available evidence
•	of the position of the origi	nal corner.	· · · · · · · · · · · · · · · · · · ·	
_	Discount of		,	
C.	Description of monumer	it for corner and accessories	established to perpetuate locating	the position of the corner:
L-12	Set Standard Kent Count	Monument in Place of Cappe	∄. d Be-rod	STATE OF MICKEY
		, and or ouppe		Co.
		ag in E root 16" W. Cherry S 2		RANDY J. KOLEHOUSE
		ag in E face 36" Beech S 40° I		LAND
	Nail & K.C. remon. t	ag in N face 36" W. Cherry S 5 ag in W face 8" Ash N 54° W 2	68" E 3,84"	SURVEYOR No.
	(160) (Official)	Surfriado o Monta 94 VV 2	0.00	25854
			 	TANKE DING SURVEYED
	Wa DI	1/1/	/ -	(25-16 - CAND SURPLINE
Signed by fracting the Chief Date 1923/73				
	•	EARTH TECH	· ·	
Surveyor's Michigan License No25854				