

SEP 18 1995

CONFIRMATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

1. Public Land Survey T 5N R 12W L-13
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

REC. OF DEEDS

8663

Register of Deeds Stamp & File Number

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:55

I, Randy Kolehhouse, in a field survey on April 5 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-13	1817	G.L.O.	L. Lyon	Set Post
	1981	L.C.R.C. #1814	Exxel Engineering	Found 7/8" x 22" Solid Rod/Set K.C. Monument
	1991	L.C.R.C. #6361	Chris Marschall	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 6/27/95

CHAIRMAN Harry Thubert

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 3/26/81 and was recorded per L.C.R.C. #1814.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-13 Found standard Kent County Monument 2' M/L South of farm fence per L.C.R.C.'s #1814 and #6361 as set by Exxel Engineering in place of 7/8" x 22" solid rod they found which checked E.H. Christ records (1902) and MDSHT plans 1955. This point is common with the N 1/4 cor., Sec. 1, T4N R12W.

L.C.R.C. #1814

L.C.R.C. #6361

Nail & KC tag in W'ly sde 16" Triple basswood N28°E 27.98'
Nail & KC tag in E sde 10" Basswood N3°E 19.24'
Nail in NE sde 8" Basswood N53°W 11.29'
Nail & KC tag in N sde 10" Basswood S71°E 33.84'
Nail & KC tag in NE sde 14" Apple S30°E 22.89'

Nail & KC tag in W sde 16" Triple Basswood N 28 E 28.05"
Nail & KC tag in E sde 12" Basswood N 3 E 19.27'
Nail in NE sde 9" Basswood N 53 W 11.29'
Nail & KC tag in N sde 10" Basswood S 71 E 33.87'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-13 Standard Kent County Monument

Nail & K.C. remon. tag on W side 18" Trip. Basswood N 28° E 28.05'
Nail & K.C. remon. tag on E side 12" Basswood N 03° E 19.27'
Nail & K.C. remon. tag on NE side 9" Basswood N 53° W 11.29'
Nail & K.C. remon tag on N side 10" Basswood S 71° E 33.87'

Signed by

Randy J Kolehhouse
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No.

25854

