

\$7.00  
\$2.00

JAN 23 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

D-8

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Randy Kolehhouse, in a field survey on April 11 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the Interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-8	1944	Wit. Map	K.C. Surveyor	2 1/2" Pipe
	1972	L.C.R.C. #198	Williams & Works	Found 1/2" Pipe in Mon. Box 0.18
				East of N-S 1/4 Line - Accepted Pipe

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/99

CHAIRMAN Harry Hubert

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-8 Found 1" iron pipe inside a 2 1/2" iron pipe 1' East of C/L Homerich Avenue running N-S and on tree row running West per  
L.C.R.C. #198. Found by Williams & Works to be 0.18' East of true N-S 1/4 line. Irons are 0.2' East and 1.7' South of the  
intersection of 1/4 lines. Accepted iron as Center Section.

L.C.R.C. #198

MBT pole S40°W 50.87'

C/L 28" Maple W 30.75'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-8 Replaced 1" iron with a standard 4" x 30" Kent County Monument

Nail & K.C. remon. tag in North side 36" Maple N 85° W 30.75'

Nail & K.C. remon. tag in SE side T. pole S 47° W 51.02'

Nail & K.C. remon. tag in SE side 14" Maple S 30° W 66.24'

Nail & K.C. remon. tag in SW side 24" Maple S 30° E 117.92'

Signed by Randy J. Kolehhouse

Date 12/22/95

EARTH TECH

Surveyor's Michigan License No. 25854

Seq. 2

REG. OF DEEDS

8886

Register of Deeds Stamp & File Number

95 DEC 28 PM 2:18

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

