

SURVEY & DOCUMENTATION

\$7.00
\$2.00

JAN 23 1996

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

COMMISSION

Kent
(County)

Located in:

Corner Code #

1. Public Land Survey T 5N R 12W D-6
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehhouse, in a field survey on March 15 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-6	1944	Wit. Map	K.C. Surveyor	2" Pipe
	1955-1966	Survey Notes	Williams & Works	Set PK per Wit. Map for Center Section
	1975	L.C.R.C. #910	Exxel Engineering	Found 1/2" Iron

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Randy Kolehhouse

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-6 Found a 1" iron pipe in the approximate C/L of Homerich Avenue running N-S per L.C.R.C. #910. Iron is 0.1 South and 0.7 East of intersection of 1/4 lines. Checks Jonker Land Surveys' measurements West and South. Accepted 1" iron as Center Section.

L.C.R.C. #910

Nail in sde P. Pole East 53.42'
Nail in sde T. Pole West 23.76'
SE cor garage NW 80.37'
C/L 10" Walnut East 42.1'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-6 Standard Kent County Monument

Nail & K.C. remon. tag in N side P. pole S 88° E 53.42'
Nail & K.C. remon. tag in S side T. pole N 85° W 23.89'
SE cor. garage N 65° W 80.50'
C/L 10" Walnut N 90° E 42.1'
Set "X" in N end conc. culvert S 20° W 57.47'
NE cor. Dse. fndn. N 30° W 123.16'

Signed by Randy J. Kolehhouse
EARTH TECH

Date 12/22/95

Surveyor's Michigan License No. 25854

REG. OF DEEDS

8885

Register of Deeds Stamp & File Number

95 DEC 28 PM 2:18

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

