

SURVEY & REMONUMENTATION

SEP 03 1999

KENT COUNTY REMONUMENTATION

ADA TWP.

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

94 JUL -5 PM 3:12

For corners in

KENT COUNTY

(County)

Located in:

Corner Code #

1. Public Land Survey

T R

T R

T R

T R

2. Property Controlling
in Section

S 35 T 7N R 10W

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Wit. Mon. on

on W. line

Sec. 35

REG. OF DEEDS
other Code #1

6957

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, William R. Byl, in a field survey on Feb. 18, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Post set at meander corner on right side of Grand River per GLO survey

No other information available from the County Surveyor's Office, other surveying firms or any other sources.

P.A. 345 1990 KENT COUNTY

PEER APPROVED 3/24/94

CHAIRMAN Harry Huber

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Did not find meander corner as set per GLO survey

No evidence of occupation or corner, set Kent County Reference Monument on line between West 1/4 corner and NW corner of Section 35.

Corner "A" on recorded survey of Sec. 35-7-10

Recorded survey L265 P20

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Kent County Reference Monument

Set Nail & KC Remon. tag top of Guard Rail Post N65°W 15.59'

Set Nail & KC Remon. tag top of Guard Rail Post S65°E 15.62'

"+" mark of Hwy. Sta. 432+00 on S. edge conc. pavement of E. bound lane S80°E 61.69'

"X" cut on top of headwall S40°W 45.70'

C/L E. bound Fulton St. is Northeasterly (at Rt. angle) 22.94'

Guard rail is Northeasterly 2'

NE'ly bank of the Grand River is South 525' m/1



Signed by

W. R. Byl

Date

06/27/94

Surveyor's Michigan License No.

23502