MAR 0 3 1998 LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION corners in SECTION <u>Kent</u> Located in: Ada Corner Code # (County) Township Public Land Survey **Property Controlling** R 10W 2303,05' South of C-6 in Section Т 3. Miscellaneous Register of Deeds Stamp & File Number Property in Sec. _, Recorded Plat Private Claims Randy Kolehouse __, in a field survey on _ November 14 do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below: NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. 11 12 Description of original monument and accessories and/or subsequent restoration: C-7 1831 G.L.O. Notes Mullett Set Post Set Witness Corners 1988 L.C.R.C. #4941 **Exxel Engineering** P.A. 345 1990 KENT COUNTY PEER APPROVED 11/20/87 This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 2/11/88 and was recorded per L.C.R.C. #4941. В. Description of corner evidence found and/or method applied in restoring or reestablishing corner: C-7 Found a Standard Kent County Monument 17' North of the edge of water of the Grand River per L.C.R.C. #4941 as set by **Exxel Engineering** L.C.R.C. #4941 Nail & tag W sde 24" Maple N 20° E 6.22' Nail & tag SW sde 28" Maple S 45° E 27.90' Nail & tag E sde 18" Maple N 10° W 60.17' Nail & tag S sde 18" Maple N 75° E 62.96' (m. 62.92') Waters edge SW 17' The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: C-7 Standard Kent County Monument Nail & K.C. remon. tag on W side 24" Maple N 20° E 6.22' RANDY I. Nail & K.C. remon. tag on SW side 28" Maple S 45° E 27.90' KOLEHOUSE Nail & K.C. remon. tag on E side 18" Maple N 10° W 60.17' Nail & K.C. remon. tag on S side 18" Maple N 75° E 62.92'

25854

Signed by

Surveyor's Michigan License No.