

\$7.00  
\$2.00

JAN 24 1996  
COMMISSION

KENT COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Prop Control 1  
other code #2

For corners in  
KENT COUNTY  
(County)

Located In:

Corner Code #

1. Public Land Survey T R  
T R  
T R  
T R  
2. Property Controlling S 9 T 7N R 12W  
In Section S T R  
3. Miscellaneous S T R  
Property in Section S T R

#2  
Wit. Mon. on  
N-S 1/4 line  
Sec. 9

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 DEC 26 PM 12:42  
REG. OF DEEDS  
8843

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat  
5. Private Claims

I, Kirk Breitels, in a field survey on Nov. 15, 1994  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current  
manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and  
5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found  
as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO Not set

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Established a point on the N-S 1/4 line of Sec. 9, T7N, R12W, 157.00' South of the C 1/4  
corner of Sec. 9. Said point is 3'± NE'ly of the NE'ly edge of pavement of Elmridge Dr.

SEE LCRC # 8842 FOR INFORMATION FOR THE C 1/4 CORNER

P.A. 345 1990 KENT COUNTY  
PEER APPROVED 11/17/94  
CHAIRMAN Harry Huber

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Standard Kent Co. Witness Monument at location described above

- Set Nail & KC Remon. tag W. side 12" Maple N15°E 21.63'  
Set Nail & KC Remon. tag S. side 24" Maple N75°E 18.98'  
Set Nail & KC Remon. tag NW side Tri. 12" Ash S50°E 12.53'  
Set Nail & KC Remon. tag S. side 12" Elm S80°W 43.81'  
Iron Pipe S80°E 33.45'



Signed by Kirk Breitels

Date 12/14/95

Surveyor's Michigan License No. 30077