

SURVEY &  
REMONUMENTATION

SEP 08 1999

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

SECTION

Kent  
(County)

Located in: Grattan Township Corner Code #

1. Public Land Survey T 8N R 9W I-10W  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
2. Property Controlling S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
in Section S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
3. Miscellaneous S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
Property in Sec. S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

REG. OF DEEDS

38 DEC 14 AM 8:00

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

other code # 12

10986

Register of Deeds Stamp & File Number

I, Randy Kolehouse, in a field survey on February 9 19 98, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-10 This corner was not originally set by the G.L.O.

1992 L.C.R.C. #6554A John Bueche Set Reference Monument  
1992 L.C.R.C. #6558 John Bueche Set K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 9/24/98

CHAIRMAN Harry Huber

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by John Bueche in August 1992 and was recorded per L.C.R.C. 6558.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-10 Found a Standard Kent County Witness Monument 300' ± East of the C/L of Lincoln Lake Avenue (bit.) on the West side of Lalley Lake per L.C.R.C.'s #6554A and #6558 as set by John Bueche on the East and West 1/4 line of Section 27, 393.70' West of the East 1/4 corner of Section 27.

L.C.R.C. #6554A

393.70' West of the E 1/4 27 on the E-W 1/4 line Sec. 27

L.C.R.C. #6558

SW corner hse. #4800 fnd. N 55° W 170.46'  
SE corner hse. #4800 fnd. N 45° W 150.55'  
NE corner hse. #4800 fnd. N 35° W 171.61'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-10 Standard Kent County Witness Monument

SW cor. hse. #4800 fndn. N 55° W 170.46'  
SE cor. hse. #4800 fndn. N 45° W 150.55'  
NE cor. hse. #4800 fndn. N 35° W 171.61'  
Nail & K.C. remon. tag on S side 24" Poplar S 60° E 137.07'  
Nail & K.C. remon. tag on N side 14" Maple N 70° E 224.53'  
Nail & K.C. remon. tag on W side 12" triple Maple South 185.33'  
C/L of bit. road, West 300'

Signed by Randy J. Kolehouse Date 9-30-98

EARTH TECH

Surveyor's Michigan License No. 25854

