FEB 1 4 1997

KENT COUNTY REMONUMENTATION

COMMISSION

VENT	COOMIT	REMONUMENTALION	

LAND CORNER RECORDATION CERTIFICATE

err	Filing Requiren	nent of Act 74, Mich. P.A. 1	1970 , 🐰	a a s
For corners in KENT COUNTY	Located In:	Corner Code #	REG. E	
 Public Land Survey Property Controlling in Section Miscellaneous 	T R T R T R T R S T R S T R S T R S T R	Wit. Mon. on S. Tine Sec. 34	DOF DEEDS	TOF MENGAN TY OF MENGAN TO FOR RECORD
Property in Section	2 I n			
5. Private Claims	Recorded Plat		A B C D E F 2 6 5 4 4 3 4 7 4 9 9	G H I J K L
do hereby certify that under rein lines 1 and 2 above were in manual of survey instructio Management or by a decree 5 above were in conformance Decree of a Court of Law; estas expressed below:	equirements of P.A. 74, Michigan P.A. conformance with regulations and rule ns of the United States Department of a Court of Law and/or that the corner with the rules of the Michigan Boal tablished, re-established, monumented comers, all in the same town and re-	es therefore as required in the curre nt of the Interior, Bureau of Lar er points mentioned in lines 3, 4 ar rd of Professional Surveyors or by d, re-monumented, recovered, four	nd 7 20 21 - 20 21 - 7 4 a 9	27 26 21 34 35 31
A. Description of origina	al monument and accessories and	d/or subsequent restoration:		•
The position of Peer Group, monu per LCRC #6575.	#6575 Marschall this corner was previou mented (Witness Monumen	Set Kent County Witnersly approved by the Kt) by Chris Marschall P.A.	f Sec. 34, T8N, R11W ess Monument on Twp. ent County Remonument on 8/5/92 and was rec 345 1990 KENT COUNTY R APPROVED 3/1/96	Line tation corded
Found Standard I Chris Marschall monumentation of LCRC #6575 Nail & KC Remo SW corner of B SW corner of H SW corner encl Nail & KC Remo SE cor. gar., Centerline of The selected lo	evidence found and/or method a Kent County Witness Mon- in place of the 1/2" I "Ridgeview Plat" and country and a second a second and a second a second and a second a second and	post, N. end Bit. (E N07°E 102. N26°E 95. Spruce N33°W 52. N 90°E 3. me and is generally	from above LCRC As s Said Iron Pipe checks s along Twp. line. 'ly of 7) N11°W 132. 81' Nail & KC Remon14' SW side 14" Oa .44' S47°E 30.45' 29' Nail & KC Remon83' E. side 22" O .00'± S02°E 71.70'	set by s with . tag .k . tag
Standard Kent Co Nail & KC Remo SW corner of B SW corner encl Nail & KC Remo SE corner gara Centerline of Nail & KC Remo Nail & KC Remo	ment for corner and accessories of Witness Monument on. tag E. side E. gate garage frame Hse. #3650 lse. #3650 osed porch frame Hse. #on. tag E. side 6" Blue lse, Hse. #3595 (SE cor. 11' wide Bit. Pavement on. tag SW side 14" Oak on. tag E. side 24" Oak	post, N. end Bit. (E N07°E N26°E #3650 N37°E Spruce N33°W	'ly of 7) N11°W 132.8 102.81' 95.14' 100.44' 52.29' 29.83' 3.00'± 30.47' 71.74'	
Signed by /w/	30077		OVED BY MICHIGAN STATE BOARD OF PROFESSION.	IAL SURVEYORS, JAN. 28, 1971
Surveyor's Michigan Lice	nse No	PONIS APPRO	APP SE HEALING OF STATE OF SHEET HORIOUR	REVISED MAY 14, 1975 REVISED JAN., 1983