

KENT COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

93 AUG 26 PM 4: 22

For corners in

Kent

(County)

Located in:

Oakfield Township

Corner Code ##

1. Public Land Survey

T _____ R _____

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous

S 27 T 9N R 9W

SW Cor., SE 1/4

SW 1/4, Sec. 27

Witness Corner

4. Lot No. _____, Recorded Plat _____

to G-11

5. Private Claims _____

REG. OF DEEDS

Pool Control
other wale #7
6826

Register of Deeds Stamp & File Number

I, Chris Marschall, in a field survey on May, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law, established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO Set post 20 Chains E. of the West line of 27 and 20 Chains E. of the
S. 1/4 Corner of 27. No Witness noted. Both in swamps 1927 Survey (W & W Notes)
shows fence to S. and W. of this point (1326' W. of S 1/4) Roosien Survey L 218
p 31 show iron set in fence lines (1326.72' W. of S 1/4)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Roosien Iron and held it for the SW corner, SE 1/4, SW 1/4, Sec. 7

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 30" Harrison Monument with witness corner cap
Nail and Tag in NW side of U.P. (5' above grade)
Nail and Tag in NE side of U.P.
Nail and Tag in NE side of 30" Poplar (5' above grade)
Center of 20' Bit. Drive to Trailer Park
Chiseled x in NW corner of concrete dumpster pad
Additional information on reverse side.

N 21°E 196.77'
S 19°E 121.02'
S 34°E 134.98'
East 28'±
S 11°E 159.54'

Signed by Chris Marschall Date May 1993

Surveyor's Michigan License No. 18661

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

SEE OTHER SIDE

682613

SECTION 27 AND 28, T9N, R9W,
 OAKFIELD TOWNSHIP, KENT COUNTY
 MICHIGAN

