

SURVEY &
REMONUMENTATION

\$7.00
\$2.00

MAY 22 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in: Oakfield Township	Corner Code #
1. Public Land Survey	T 9N R 9W	Witness Mon.
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	443.37 South of K-8
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

"other" #12

11654

Register of Deeds Stamp & File Number

I, Randy Kolehouse, in a field survey on July 15 19 99,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as
required in the current manual of survey instructions of the United States Department of the interior,
Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned
in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors
or by a Decree of a Court of Law; established, re-established, monumented, re-monumented,
recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-8	1837	G.L.O. Notes	Cathcart	Set Post
	1848	N/A	Caukin	Corner Set at Mid-Point
	1950	Assessor's Plat L. 47 P. 28	Williams & Works	Set Plat Monument
	1987	L.C.R.C. #4540	Thomas Chettleburgh	Fnd. Plat Monument / Set K.C. Witness Monument
	1989	L.C.R.C. #4944	Harvey Hubers	N/A
	1994	L.C.R.C. #7241	Glaza & Associates	N/A
	1994	L.C.R.C. #7242	Glaza & Associates	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 7/29/99

CHAIRMAN Harvey Hubers

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Thomas
Chettleburgh on 11/17/87 and was recorded per L.C.R.C. #4540.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-8 Found a Standard Kent County Witness Monument 180' ± South of the South edge of Chain Lake, on line of a tree row and brush line
running South, per L.C.R.C.'s #4540 and #7242 as set by Thomas Chettleburgh over a plat monument which checked Assessor's
Plat L. 47 P. 28.

L.C.R.C. #4540

L.C.R.C. #7242

Nail/tag W side 23" Willow N5°E 18.70'
SW cor Cottage foundation N89°E 14.82'
Nail/tag E side 7" Oak S3°W 18.16'
NE cor Cottage foundation S13°W 34.03'
Nail/tag NW side Power Pole S60°W 26.17'
Nail/tag N side Power Pole N69°W 108.24'

Nail & K.C. remon tag in W side 23" Willow (stump) N05°E 18.70' (m. 18.73')
SW corner cottage foundation N89°E 14.82' (m. 14.75')
Nail & K.C. remon tag in E side 10" Oak S03°W 18.16' (m. 18.22')
NE corner cottage foundation S13°W 34.03' (m. 34.05')
Nail & K.C. remon tag in NW side P. pole S60°W 26.17' (m. 26.24')
Nail & K.C. remon tag in N side P. pole N69°W 108.24' (m. 108.22')

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-8 Standard Kent County Witness Monument

Nail & K.C. remon. tag on W side 23" Willow stump N 05° E 18.73'
SW cor. cottage frdn. N 89° E 14.75'
Nail & K.C. remon. tag on E side 12" Oak S 03° E 18.22'
NE cor. cottage frdn. S 13° W 34.05'
Nail & K.C. remon. tag on NW side P. pole S 60° W 26.24'
Nail & K.C. remon. tag on N side P. pole N 69° W 108.22'

South edge of Chain Lake, North 180' ±
On tree row and brush line running S

Signed by Randy J. Kolehouse
WILLIAMS & WORKS
Surveyor's Michigan License No. 25854

Date 10-22-99

