

MAY 22 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in: Courtland Township	Corner Code #
1. Public Land Survey	T <u>9N</u> R <u>10W</u>	<u>J-11W</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	<u>952.56 West</u>
	S _____ T _____ R _____	<u>Of J-11</u>
3. Miscellaneous	S _____ T _____ R _____	_____
Property in Sec.	S _____ T _____ R _____	_____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on February 3 19 99, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-11	1837	G.L.O. Notes	Cathcart	Set Post
	1996	L.C.R.C. #9409	Kirk Breitels	N/A
	1996	L.C.R.C. #9411	Kirk Breitels	Set K.C. Witness Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Kirk Breitels on 10/30/96 and was recorded per L.C.R.C. #9411.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-11 Found a Standard Kent County Witness Monument per L.C.R.C.'s #9409 and #9411 as set by Kirk Breitels.

L.C.R.C. #9411

Nail & KC Remon. tag SW side 36" Willow cluster N60°W 63.58' (m. 63.54')
Nail & KC Remon. tag W. side 12" dead tree N00°E 33.36' (m. 33.38')
Nail & KC Remon. tag W. side 12" Elm S05°E 67.20' (m. 67.17')
Nail & KC Remon. tag SW side 20" Pine S50°E 196.56' (m. 196.54')
Nail & KC Remon. tag NW side 18" Pine N50°E 178.57' (m. 178.53')
East edge of cultivated field is West 6'+/-
Top of slope- slope down to East- is East 6'+/-

P.A. 345 1990 KENT COUNTY
PEER APPROVED 2/25/99
CHAIRMAN Randy Kolehouse

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-11 Standard Kent County Witness Monument

Nail & K.C. remon. tag on SW side 36" Willow cluster N 60° W 63.54'
Nail & K.C. remon. tag on W side 12" dead tree N 00° W 33.38'
Nail & K.C. remon. tag on W side 12" Elm S 05° E 67.17'
Nail & K.C. remon. tag on SW side 20" Pine S 50° E 196.54'
Nail & K.C. remon. tag on NW side 18" Pine N 50° E 178.53'
East edge cultivated field West 6'+/-
Top of slope - slope down to East - East 6'+/-

Signed by Randy J. Kolehouse Date 9-27-99

WILLIAMS & WORKS

Surveyor's Michigan License No. 25854

