

MAY 22 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE

For c	orners in	الم المحلة ومنطأ المحلة .	Filing Requirement KENT COUNT		159		
	Kent		Located in: Nelson C	Corner Code #	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	303	
		ounty)	Township	,	AMIO	5건경 2종을	
1. 1	Public Lar	ed Survey	T R	H-13	AMIO: 01		
	Property C	Controlling S	T R		11519		
3. i	Miscellaneous STR				- -		
Į	Property in	n Sec. S	TR		Register of Deeds Stamp & File N	umber	
			d Plat		A B C D E F G H J	JKL	
		i					
						-2	
į	Randy Ko	olehouse in a					
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points					ts 5 10	11 12-	
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as					35		
required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned)r,		
			mance with the rules of the Mic				
			established, re-established,	monumented, re-monumente	d, , 1927 20 21 22 1	_232	
	,	d as expressed below:			10		
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.					11		
	· On the	ns cerumcate.			12 33 33 34	25 25	
A.	Descript	tion of original monur	ment and accessories and/or	r subsequent restoration:	13	ĨĨ	
H-13	1837	G.L.,O. Notes	Cathcart	Set Post			
	N/A	Records	Consumers Power	Set "U" Shaped Steel f	ost		
	1985	L.C.R.C. #4353	Glen Hackbardt	"U" Iron			
	1986	L.C.R.C. #4444	Randy Kolehouse	Fnd. "U" Iron / Set K.C.		-	
	1988	L.C.R.C. #4749	John Bueche	K.C. Monument	P.A. 345 1990 KENT COUN		
					PEER APPROVIED 10/25/	199	
	(CHAIRMAN Family	ulu	
			roved by the Kent County Rei led per L.C.R.C. 4444.	monumentation Peer Group	and monumented by Randy Koleho	ouse ·	
B.	Descrint	ion of corner evidenc	e found and/or method appl	ied in restoring or reestabl	ishing corner:		

H-13 Found a Standard Kent County Monument on the C/L of 16 Mile Road extended 40' ± East of the East end of gravel road per L.C.R.C.'s #4444 and #4749 as set by Randy Kolehouse in place of a "U" iron he found which checked L.C.R.C. #4353 and the records of Consumers Power.

L.C.R.C. #4444

Nail & K.C. Remon. tag in W, side 8" W, Cherry S 10° W 7.75' Nail & K.C. Remon. tag in SW side 12" Basswood S 45° E 17.76'

Nail & K.C. Remon. tag in N. side 10" Oak S 80° E 18.75'

Nail & K.C. Remon, tag in E. side 20" Basswood N 10° E 63.44"

K.C. Mon. at N 1/4 cor. section 3 T9N R10W East 120.25'

L.C.R.C. #4749

Nail & K.C. Remon tag in W sde 10" W. Cherry S 10 W 7.75' (m. 7.74')

Nail & K.C. Remon tag in SW sde 14" Basswood S 45 E 17.76' (m. 17.74')

Nail & K.C. Remon tag in N sde 12" Oak S 68 E 18.75' (m. 18.70')

Nail & K.C. Remon tag in E sde 22" Basswood N 10 E 63.44' (m. 63.43')

K.C. Mon at N 1/4 cor. sec. 3, T9N, R10W, E 120.25'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-13 Standard Kent County Monument

Surveyor's Michigan License No

Nail & K.C. remon. tag on W side 10" W. Cherry S 10° W 7.74'

Nail & K.C. remon, tag on SW side 14" Basswood S 45° E 17.74"

<u>2585</u>4

Nail & K.C. remon. tag on N side 12" Oak S 68° E 18.70'

Nail & K.C. remon. tag on E side 22" Basswood N 10° E 63.43'

K.C. Mon., H-1, T9N, R10W, East 120.25'

Signed by WILLIAMS & WORKS

RANDY J KOLEHOUSE LAND