



Signed by

Surveyor's Michigan License No.

30077

MAY 22 2000

## KENT COUNTY REMONUMENTATION

00	
	SECTI

		58 图 9
SECTION LAND CORNER RECORDATION CE		
Filing Requirement of Act 74, Mich.	.P.A. 1970	C miles
KENT COLINTY	n o a	्रे ज चंद्र
Located In: Corner Code #		
4 Dublic Land Curvey T P	ED.	· · · · · · · · · · · · · · · · · · ·
1. Public Land Survey	"> + d + 6"	: 50 ORD
TR	Corner #	18
2. Property Controlling S 1 T 10NR 11W Wit. Mon. on in Section S T R N-S 1/4 Line		<i>∧</i> , ==
3. Miscellaneous S T R (Solon Twp.)	115	<b>3</b> 5
Property in Sec. S TR	Register of Dee	ds Stamp & File Number
		'
4. Lot No, Recorded Plat	ABCDE	F G H I J K L
5. Private Claims	1	1 3 2
	3	
1, Kirk Breitels , in a field survey on Nov. 1 , 19 99 do hereby state to	- 1 1 1 1 1	- 9101212
requirements of P.A. 74. Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 abov	re were in _	
conformance with regulations and rules therefore as required in the current manual of survey instruction. United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Land	iw and /or 6	-16 15 14 13
that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, mon	Michigan [	
recovered, found as expressed below:	8 - 19 - 20 -	-21222324-
NOTE: Not more than 2 corners, all in the same town and range, may be recorded	9	
on this certificate.	10 30 29	-28272625-
	11	
	12 31 32	-33343536-
A. Description of original monument and accessories and/or subsequent restoration:	13	
No Information	P.A. 345 1990 KEN	r county
No information	PEER APPROVID	9/23/99
	PEER APPROVE	2 Lulier
· ·	CHAIRMAN To	
		,
B. Description of corner evidence found and/or method applied in restoring or reestabli Established location on N-S 1/4 line (E. line of SW 1/4) - computed C 1/4	shing corner: corner at Intersection of 1/4 lis	nes.
839.56' to S 1/4 corner		
1802.29' to C 1/4 corner (computed)		'
The above location is accepted by me and is generally accepted by professi	onal surveyors as the best ava	ilable evidence
of the position of the Witness Corner.		
		* 1
C. Description of monument for corner and accessories established to perpetuate locati	ng the position of the corner:	water (State Commun.)
Set Kent County Witness Monument as described above	. 12.0	OF MICH
Nail & KC Remon. tag E. side 40" Oak N00°E 50.02'		C.P.
Nail & KC Remon. tag S. side 12" Pine S60°E 38.09' Nail & KC Remon. tag SE side 15" Oak S50°W 21.49'	# * /	KIRK BREITELS
Nail & KC Remon. tag NE side 27" Oak N45°W 49.48'		LAND \$
In remains of North-South fence line and stump row		SURVEYOR 1
South edge of swamp is North 75' ±.		30077
, , , , ,		TO THE PARTY OF TH
1/1 RD	1 1	The state of the s
	15/1/01	

Date