

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Keweenaw (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 34 T 56N R 31W	2
	S 34 T 56N R 31W	H12
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33				35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 09/11/13 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(2-Sec. 34) East 1/16 corner between Sections 27 and 34. Not previously monumented.

(H12) Center of Section 34. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(2-Sec. 34) Established the position for the corner midway and on the Section line between Section
corner 1312.14' east and Quarter corner 1312.14' west.

(H12) Established the position for the corner at the intersection of 1/4 lines of Section 34. The
bearing of the E-W 1/4 line is the weighted mean of the north and south Section lines. The bearing
of the N-S 1/4 line is the weighted mean of the east and west Section lines.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(2) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Cedar S67°E 2.8' mrkd "1/16S BT"
11" Cedar S02°E 12.05' do
7" Maple S56°W 16.3' do
5" Maple N89°W 18.45' do
Set sq'd cedar post adjacent.
E= 7907606.206 N= 270929.417

(H12) Set 1"IDx32" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
2" B.Spruce N17°E 16.95' mrkd "C1/4 BT"
3" W.Birch S67°E 31.8' do
6" B.Spruce S24°E 35.35' do
5" Tamarack S22°W 33.7' do
Set sq'd cedar post adjacent.
E= 7907210.204 N= 270139.410

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).
Coord. Ref.=USACE monument "RAMP 1995": N= 268244.768 m. E= 7906171.601 m.

Signed by Stephan J. Szyszkoski Date 10/02/2013
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division