

SURVEY &
REMONUMENTATION

APR 28 1995

COMMISSION

1994 REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD

94 DEC 22 PM 2:05

LIBER NO. 05 PAGE NO. 181

REGISTER OF DEEDS
LAPEER COUNTY, MICHIGAN

For corners in MARATHON TWP.
LAPEER (County)

Located In:

Corner Code #

1. Public Land Survey

T 09N R 09E

M-8

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

Register of Deeds Stamp & File Number

4. Lot No. Recorded Plat

5. Private Claims

I, JONATHAN N. FIELD, in a field survey on SEPTEMBER 23 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management, or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law, established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1852 GLO; WAMPLER, D.S.; SET 1/2 MILE POST; BEECH 6 S35W 5LKS., BEECH 14 N28W 24LKS.
1906 SICKLESTEEL, C.S.; STAKE; PINE 30 S72 1/2W 44LKS., PINE 36 S17E 64LKS.
1973 HENDERSON-BATES; HENDERSON, P.S.#16043; SURVEY L.2, PG.178; 1/2" RE-ROD; N70°W 24.23'
12" CATALPA, S25°W 89.79' 40" OAK, N80°E 51.02' 18" APPLE
1973 HENDERSON; LCRC L.2, PG.289; END 1/2" RE-ROD; SAME WITS AS 1973 SURVEY ABOVE
1976 HENDERSON-BATES; HENDERSON, P.S.#16043; SURVEY L.3, PG. ; END 1/2" ROD; N40°E 43.5'
24" PINE, S25°W 89.79' 40" OAK, N70°W 24.23' 12" CATALPA
1978 BECK-GRAVLIN; GRAVLIN, P.S.#23510; SURVEY L.4, PG.546; END 1/2" IRON; N70°W 24.22' 12"
CATALPA, S20°W 80.88' 40" OAK, N45°E 43.94' 26" PINE
1980 BECK-GRAVLIN; BECK, P.S.#21559; SURVEY L.5, PG.913; 1/2" IRON; N70°W 24.22' 12" CATALPA,
S20°W 89.85' 40" OAK, N45°E 43.94' 26" PINE
1988 GRAVLIN, P.S.#23510; SURVEY L.7, PG.887; END 1/2" IRON; N70°W 24.22' 12" CATALPA, S20°W
89.88' 40" OAK, N45°E 43.94' 26" PINE

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 1994 ROWE ENG.; FIELD, P.S.#37276; END 1/2" ROD (BENT) 5' W. OF C/L GRAVEL ROAD N-S & ON
TREE/FENCE LINE TO W. RECOVERED 2 PREVIOUS WITNESSES INDICATING THAT END ROD IS IN
SAME POSITION AS 1973 HENDERSON-BATES SURVEY

2628.50' M-8 TO M-9 (MEAS. BY OTHERS)
2658.95' M-8 TO M-7 (MEAS. BY OTHERS)

ACCEPTED 1/2" ROD AS A CAREFUL AND FAITHFUL PERPETUATION OF THE ORIGINAL CORNER POSITION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- M-8 REMOVED BENT ROD SET 1/2" ROD W/ STANDARD BRASS CAP
N70°W, 24.12' SET NAIL W/ REMON TAG ABOVE END NAIL W/FLAG. IN S. FACE 16" CATALPA
S25°W, 88.76' SET NAIL W/ REMON TAG IN E. FACE 48" OAK
N50°E, 43.40' SET NAIL W/ REMON TAG IN NW FACE 30" PINE
S20°E, 118.73' SET NAIL W/ REMON TAG IN W. FACE T. POLE
NORTH, 120.26' END 1/2" ROD (BENT & CORRODED, REPLACED W/ 1/2"X 18" ROD)

PEER GROUP
APPROVED LAND CORNER

PA 345 OF 1990

LAPEER COUNTY

Signed by Jonathan N. Field
Surveyor's Michigan License No. 32276

Date 12-8-94

DATE 12-22-94

LIBER 0005 PAGE 0181

