

## MAY 28 1997

## MORNING WAR

## 1996 REMONUMENTATION PROGRAM LAND CORNER RECORDATION CERTIFICATE

RECEIVED FOR RECORD

Filing Requirement of Act 74, Mich. P.A. 1970

96 DEC 27 PH 1: 19

For corners in DEERFIELD T	Located In:	Corner Code #			Me	lissa I	De Ven	ah	
(County)				Melissa. De Vaugh REGISTER OF DEEDS LAPEER OF WITH, HIGHIGAN					
					LAPEE	ទីវីទីឯ	TV, HR	Higan	
1. Public Land Survey	T <u>09N R 10E</u>	A-2							
	T R	<del></del>							
	T R		,						
2. Property Controlling S	T R T R	<del></del>							
			<b>D</b> 1.6						
	T R		Registe	r or De	eas 5	tamp 8	HILE	eamur	Γ
	T R		· · · · · · · · · · · · · · · · · · ·						
· · · · · · · · · · · · · · · · · · ·		·							
<ol> <li>Lot No, Recor</li> <li>Private Claims</li> </ol>			_ ,	A B (	D	E F G	H !	JK	L M
5. Private Claims		. ,	2	···-6	5	4	3	2	
			3			,			
. JONATHAN M. FIELD	in a field s	urvey on <u>AUGUST</u> 19 <u>96</u>	_ , 4	. <del>7</del>	8	ý	10	11	12
do hereby certify that under requi	irements of P.A. 74, Michigan	P.A. of 1970, the corner points mention	ned 5		:		:		<u> </u>
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as					- 17 -	- 16	·· 15·	14	13
					:			<del></del>	
					-20	21	22	23	24
expressed below:			9					<del> </del>	
	M * 4P		10 11	30	29	28	27	26	25
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.				-		-		<del> </del>	
on the continues.			12	31	32	33	34	35	36
A. Description of original n		s and/or subsequent restoration:	13		•		-		
<b>4.1.2</b> ,				, t-		<b></b>			
			APPE		er Gr	quor			
				PA 3	AS OF	1990 1990	HNE	R	
			4,	MPE		TNUC	) \/		
			Mille	,/	17				
			AY DIP	VIC D	2 2		<del></del>		
		,	74 TE 1	7 IO で <b>ロ</b> ごつ	.3. U(	ノ、SUI ノ	HVEY	C .	
		(	<i>が</i> りに <u></u>		· ( * 7	0			

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: 1996 ROWE ENG.; FIELD, P.S.#37276; FND. STONE WITH CROCKERY, GLASS, AXE HEAD & OTHER OLD PIECES OF IRON; 4' E. OF C/L WILLITS ROAD N-S, FIELD LINE TO E. HELD HIGH POINT OF STONE.

A-2 TO A-1 3504.07'

A-2 TO A-3 2651.24'

ACCEPTED FND. STONE AS BEST EVIDENCE OF ORIGINAL CORNER POSITION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-2 REPLACED STONE W/ 1/2" ROD & STANDARD REMON CAP S55°E, 60.16' P-K NAIL W/TAG #37276 IN NE FACE P.POLE

N75°W, 28.47' P-K NAIL W/TAG #37276 IN NE FACE P.POLE

S35°W, 53.07' P-K NAIL W/TAG #37276 IN SE FACE 20" ELM

N45°E, 21.21' 1/2" ROD

JONATHAN
M. FIELD
PROFESSIONAL
SURVEYOR
No.
37278

Signed by Janutu	1	ntil
Surveyor's Wichigan License		

12-2-96.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971