

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

<u>Luce</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S <u>3</u> T <u>46N</u> R <u>10W</u> S <u>3</u> T <u>46N</u> R <u>10W</u> S _____ T _____ R _____	<u>8</u> <u>11</u> _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____ _____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 09/17/13 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 3) West 1/16 corner, Section 3. Not previously monumented.

(11-Sec. 3) Southwest 1/16 corner, Section 3. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 3) Established the position for the corner midway and on a straight line between Quarter
corner 1317.80' west and the intersection of 1/4 lines of Section 3 1317.80' east. The old Charcoal
Grade is approx. 50' west of the corner.

(11-Sec. 3) Established the position for the corner at the intersection of straight lines connecting
opposite 1/16 corners. The old Charcoal Grade is approx. 27' west of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Cherry S60°E 15.05' mrkd "W1/16 BT"
9" B.Spruce N01°E 5.9' do
5" Maple N30°W 20.2' do
8" W.Birch S50°W 16.0' do
Set 4" cedar post adjacent.
E= 8111726.601 N= 181935.185

(11) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
12" Maple S84°W 18.55' mrkd "SW1/16 BT"
7" Maple N06°E 28.35' do
9" B.Spruce N88°E 28.9' do
8" B.Spruce S45°E 19.0' do
Set 4" cedar post adjacent.
E= 8111737.096 N= 181534.969

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).
Coord. Ref.=NGS PID RJ0491: N= 184295.144 m. E= 8114483.019 m.

Signed by Stephan J. Szyszkoski Date 10/15/2013
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division