

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Luce (County)	Located In:	Corner Code #
1. Public Land Survey	T 46N R 10W T 46N R 11W T _____ R _____	A5 same M5 corner
2. Property Controlling in Section	S _____ T _____ R _____ S _____ T _____ R _____ S _____ T _____ R _____	_____ _____ _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____ _____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Stephan J. Szyszkoski, in a field survey on 06/07/2010 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(A5) Corner common to Sections 7-18 T46N-R10W and Sections 12-13 T46N-R11W. 1841 - Established by
W.A.Burt Deputy Surveyor. Set post. Hemlock 14" N45E 50 links, Fir 10" N25W 33 links. 1974 -
Remonumented by Billy D. Buckler RLS at record bearing and distance from possible Hemlock B.T. Calls
to swamp edges check. Set 1"IDx36" I.pipe with 4" alum. cap. 12" W.Pine N30E 59.4', 6" Maple S45E
29.5'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(A5) The original post and accessories were not recovered. Found the 1974 monument in good condition
and at record bearing and distance from the 1974 witnesses. The Maple NBT SE is in good condition.
The W.Pine NBT is an indefinite rotted stump. Accepted the monument as a careful and faithful
perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(A5) Fd. 1"ID I.pipe w/ 4" alum. State of MI cap.
Set measuring nail with MDNR tag in the side of:
12" Maple S40E 29.6' mrkd "S18" 1974 NBT
7" Cedar S54W 8.6' mrkd "S13 NBT"
7" Maple in clump N35W 6.55' "S12 NBT"
6" Balsam N84E 9.6' "S7 NBT"
Bearings are magnetic.



Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 10/26/2010

For the Michigan Department of Natural Resources and Environment, Forest Management Division