

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Luce	Located In:	Corner Code #
(County)		
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 31 T 50N R 8W	4
	S 31 T 50N R 8W	8
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 08/04/2008 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(4-Sec. 31) Northwest 1/16 corner, Section 31. Not established in the original survey.

(8-Sec. 31) West 1/16 corner, Section 31. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(4-Sec. 31) Established the corner at the intersection a straight line between 1/16 corners #3 and #5 of Section 31 with the West, N-S 1/16 line Section 31. The location of the West, N-S 1/16 line is such as to make the areas of the fractional SW1/4 of the SW1/4, the NW1/4 of the SW1/4, and the SW1/4 of the NW1/4 proportional to the acreages given on the face of the original U.S. Government Plat.

(8-Sec. 31) Established the corner at the intersection of a straight line between East and West 1/4 corners of Section 31 with the West, N-S 1/16 line of Section 31. The location of the West, N-S 1/16 line is such as to make the areas of the fractional SW1/4 of the SW1/4, the NW1/4 of the SW1/4, and the SW1/4 of the NW1/4 proportional to the acreages given on the face of the original U.S. Government Plat.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(4) Set 1"ID X36" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
7" R.Pine N75W 25.4' mrkd "NW1/16 BT"  
8" W.Birch S37W 4.25' do  
5" W.Pine S62E 10.85' do  
10" J.Pine S70W 19.8' (slope) do  
Bearings are magnetic.

(8) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
8" Oak N08E 4.42' mrkd "W1/16 BT"  
8" R.Pine S75W 6.47' do  
4" R.Pine S56E 2.88' do  
10" W.Pine N66E 10.39' do  
Bearings are magnetic. The monument is stamped with an Oct. 2007 date.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 11/18/2008

For the Michigan Department of Natural Resources, Office of Land and Facilities

