Surveyor's Michigan License No.

MAR 1 3 1998	MACKIN	AC COUNTY RE	MONUME	NTATIO)	N CORNER	
~ ***	LA	AND CORNER RECO	RDATION CE	ERTIFICAT	E	
SECTION For corners in	Fi	ling Requirement of	Act 74, Mic	h. P.A. 197	Order A B. FILED	
Mackinac County)	Løcated	In: Corn	er Code ##	MAC"		
Public Land Survey	T T 41N	R Section Section I R 3W#6 WCM	4C A13/B13	A17 713	DEC 29 1997 PM	
 Property Controlling in Section Miscellaneous Property in Sec. 	S T S T S T S T	_ R	On 31	R	egister of Deeds Stamp & File No	ımber
4. Lot No,	Recorded Plat				– ABCDEFGHI	JK
5. Private Claims				·	_ 2 _ 6 _ 5 _ 4 _ 3	-2
Neil E. Hill		DECEMBER	22 97		3	-11
do hereby certify that under rin lines 1 and 2 above were current manual of survey ins Management or by a decree of above were in conformance of Court of Law; established, expressed below: NOTE: Not more than 4 on this certificate	in conformance with a tructions of the United of a Court of Law and/or with the rules of the Mic re-established, mont corners, all in the sa	Michigan P.A. of 1970, the regulations and rules the States Department of the that the corner points mechigan Board of Land Surumented, re-monumented	refore as required interior, Burea ntioned in lines reyors or by a Ded, recovered,	nentioned red in the u of Land 3, 4 and 5 ecree of a found as	5 6 18 17 16 15 7 8 19 20 21 22 9 10 30 29 28 27 11 12 31 32 33 34	-23
A. Description of origina 1840 GLO notes	l monument and acc William Bur		marack	tion: N58½W S84W		
Line for corner is shown No records of corner to GLO distance 805.20	being perpetuated.					
B. Description of corner	evidence found and	/or method applied in i	restoring or re	establishin	g corner:	
1997 Found P.K. monument box & rod Corner set at 631.91's	l with re-monume	ntation cap.	d the Easter	dy ROW	line of Bus I-75. Checked p	ositic
Plat concrete monume					ACCEPTED BY THE MACKINAC OSURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER PA. 345 OF 1990 AT A MEETING HELD ON	TAUO:
i ·						
C. Description of monum	ent for corner and a	ccessories established	i to perpetuate	e locating th	ne position of the corner:	
Utility pole S45E	37.20' N	n Line and Easterly W Brick Cor Buildi O" Spruce		f Bus I-75 54.96' 71.26'	i. Set rod & cap and monume	ent bo

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, REVISED MAY 14, REVISED JAN.

HILL

Land Surveyor No. 27447