

SURVEY &
REMONUMENTATION

OCT 11 1994

COMMISSIONER

MACKINAC COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac
(County)

Located In:

Corner Code #

1. Public Land Survey T 40N R 4W MC G-4/G-5
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

RECEIVED & FILED
DIANE FRANKOVICH
MACKINAC COUNTY CLERK OF DEEDS

SEP 6 1994
AM PAI
7/8/9/10/11/12/13/14/15/16

Register of Deeds Stamp & File Number

Neil E. Hill

August 22 19 94

I, in a field survey on , 19 ,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Set Meander Corner at 78.50 ch then offset 1.50 ch.

Set post

Tied 4" Fir N43E 0.17 ch
3" Fir N25W 1.0 ch

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Parole evidence indicates that a steel jacket water tank was set at the Section Corner location
by Ford Huyck and his father.

This location is indicated on the Josephine Levellie Plat. It has been used as the Section
Corner and is located in the Moran River.

1976 Feindt survey to North; recorded meander corner 98.51' North.

1977 Connell MDOT recorded Liber B, page 65.

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 8-16-94

James H. Kranger

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" re-rod with 4" aluminum cap 132.00 feet North of steel water jacket on N-S Section
line. Corner falls on Northerly bank of Moran River. Distances are slope distances from
objects to four feet above corner.

8" Spruce N50E 51.08'
P.Pole N15E 55.18'
3" Spruce N10E 41.18'
6" Cedar N10W 61.47'



Signed by Neil E. Hill P.S.

Date August 22, 1994

Surveyor's Michigan License No. 27447

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

09-06-94 1CL3183

MSBR

D-0277