

MAY 20 1997

COMMISSION

MACKINAC COUNTY REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac
(County)

Located In:

Corner Code #

1. Public Land Survey

T 40N R 4W

P.C.C. #6

T _____ R _____

NW Cor. P.C. #6

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

#30

RECEIVED & FILED

DIANE FRANKOVICH
MACKINAC COUNTY REGISTER OF DEEDS

NOV 15 1996

AM _____ PM _____

7|8|9|10|11|12|1|2|3|4|5|6

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Neil E. Hill, in a field survey on SEPTEMBER 30, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO notes. N33W 14.30 ch. Set post (943.60 feet).

14" Birch S79E 14 lks

14" Birch N37W 14 lks

See sketch on reverse.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of corner.

Set corner at prorated position between the NW corner of P.C. #4 and the NW corner of P.C. #7.

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 9-30-96

James H. Chandler

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


Set with 5/8" rerod and 4" aluminum cap.

Property iron #16041 S18E 3.72'

1 1/4" Pipe N30W 2.03'

P. Pole N25W 14.16'

3" Cedar N65E 3.73'



Signed by Neil E. Hill P.S. P.C. Date _____

SEPTEMBER 30, 1996

Surveyor's Michigan License No. _____