

MACKINAC COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac
(County)

Located In:

Corner Code ##

RECEIVED & FILED
DIANE FRANKOVICH
MACKINAC COUNTY REGISTER OF DEEDS

NOV 15 1996

AM PM
7/8/9/10/11/12/1/2/3/4/5/6

1. Public Land Survey T 40N R 4W
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

PCC L-4/L-5
South 1/4 Cor Sec 12
on North line of PC 19

#31

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Neil E. Hill, in a field survey on SEPTEMBER 30, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. notes. From Sec. 11 & 12 intersection with the North line of P.C. 19 to Sec. 12 & Sec. 7 intersection with the North line of P.C. 19 meas. 81.89 ch (5404.74 feet) 2702.37 feet for 1/4 Corner.
Wilcox survey 1975.

Recorded Liber A, Page 185.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Wilcox set.

1/2" iron by parole evidence in centerline of road & on fence line North

PP N60W 66.96'

W. Birch S40W 68.24'

Measures 2689.10 feet to Sec. Corner to NE (2702.37' GLO)

Accepted corner as found.

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 9-30-96

James H. Kravger

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1/2" iron rod in place with cap #14102.

New PP N60W 65.02'

6" W. Birch S25W 68.07'

6" Poplar N05E 40.57'

8" Scribed Poplar S10E 46.03'

SURVEY &
REMONUMENTATION

MAY 20 1997

COMMISSION



Signed by Neil E. Hill P.S. P.C. Date _____

27447

SEPTEMBER 30, 1996

Surveyor's Michigan License No. _____