

MACKINAC COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac
 (County)

Located In:

Corner Code #

1. Public Land Survey T 40N R 4W P.C.C. M-4/M-5
 T _____ R _____
 T _____ R _____ Section Corner _____
 T _____ R _____ common to _____
 2. Property Controlling S _____ T _____ R _____
 in Section S _____ T _____ R _____ Sec's 12 & 7 and
 3. Miscellaneous S _____ T _____ R _____ North line of PC 19
 Property in Sec. S _____ T _____ R _____
4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

#33

RECEIVED & FILED
 DIANE FRANKOVICH
 MACKINAC COUNTY REGISTRE OF DEEDS

NOV 15 1996
 AM _____ PM _____
 7|8|9|10|11|12|1|2|3|4|5|6

Register of Deeds Stamp & File Number

I, Neil E. Hill, in a field survey on SEPTEMBER 30, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. notes. South along East side Section 12 intersected P.C. 19 at 45.68 ch (3014.88')
Set post.
 12" Birch S23W 12 lks
 6" Cedar S68W 5 lks
 Corner by Wilcox 1975.

Recorded Liber A, Page 185.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found corner by Wilcox. 1/2" iron with cap #14102.
 Guard post West 13.40'
 Guard post N45W 20.37'
 Guard post S30W 26.00'
 23.9' East of E.M. N.B. Lane I-75.

Accepted corner location

ACCEPTED BY THE MACKINAC COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER P.A. 345 OF 1990 AT A MEETING HELDON 9-30-96

James H. Ganger

Also recorded in: T40N, R3W, P.C.C. A-4/A-5

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced corner with 5/8" re-rod and 4" aluminum cap.
 Top of guard post S20W 26.73'
 Top of guard post S35W 16.43'
 Top of guard post S85W 11.67'
 Top of guard post N50W 17.68'

SURVEY &
 REMONUMENTATION

MAY 20 1997

COMMISSION



Signed by Neil E. Hill P.S., P.C. Date SEPTEMBER 30, 1996
 Surveyor's Michigan License No. 27447