

SURVEY & REMONUMENTATION

MAR 13 1998

MACKINAC COUNTY REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECTION

Mackinac
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 41N R 3W (#5) WCMC A-7/A-8

T R Section 19

Also recorded as

T 41N R 4W (#5) WCMC M-7/M-8 ✓

T R Sections 24

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

RECEIVED & FILED
DIANE FRANKOVICH
MACKINAC COUNTY REGISTER OF DEEDS

DEC 29 1997
AM PM
7/8/9/10/11/12/13/14/15/16

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Neil E. Hill

DECEMBER 22 97

I, Neil E. Hill, in a field survey on DECEMBER 22, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1840 GLO notes William Burt 5" W. Birch Meander Corner
1984 James Granger set 1/2" re-rod with cap #16041
Recorded Liber C, page 75

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1997 Found re-rod with cap. 3' from water
DNR sign post N45W 66.92 feet
8" Cedar S55W 75.42 feet
12" Bent cedar S22E 105.22 feet
10" Spruce S55E 36.43 feet

Recorded as 2319.90' from 1/4 Corner to South

Moved corner away from water's edge.


ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 12-12-97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 1/2" re-rod and remonumentation cap 48' from shore of Lake Huron.

Re-set at 2275.00' from 1/4 Corner.

8" W. Birch S35E 41.58'
8" Cedar S70E 23.27'
8" Bent Cedar N70E 29.02'
8" Cedar N80W 60.90'



Signed by Neil E. Hill P.S.

Date

DECEMBER 22, 1997

Surveyor's Michigan License No.

27447