

JAN 21 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Mackinac County Remonumentation Corner

For corners in

Mackinac County

Located in:

Corner Code #

1. Public Land Survey

T42N R01W

MC E-5/F-5

#2

2. Property Controlling
in Section

S

T

R

3. Miscellaneous

S

T

R

Property in Sec.

S

T

R

4. Lot No. , Recorded Plat

5. Private Claims

RECEIVED & FILED
DIANE FRANKOVICH
MACKINAC COUNTY REGISTER OF DEEDS

DEC 31 1998

AM

PM

7/8/9/10/11/12/1/2/3/4/5/6

Register of Deeds Stamp & File Number

I, Neil E Hill, in a field survey on 12-21-98, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845 GLO Notes James Mullett 12" W Pine for Meander Post

1956 DNR Billy Buckler 13" Cedar N 28 W 36 lks
1" Iron Pipe w/ 4" Brass Cap 12" W Pine N 41 E 87 lks
On East shore of Bay City Lake
Liber 2, Page 305

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER PA.
345 OF 1990 AT A MEETING
HELD ON 12-04-98 NEH

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


1998 Fd DNR corner

Corner was found on-line but at an incorrect distance of 927.00 feet from section cor to West
New MC was set, on-line between the section and ¼ corners, at a pro-rated GLO distance

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a ½" re-rod with 4" Alum. remonumentation cap
Corner is approx 220' from the East shore of Bay City Lake

6" Spruce N 05 E 6.54'
8" Poplar S 20 W 14.40'
16" Poplar S 40 E 17.08'
12" W Birch N 75 W 35.20'
1" DNR pipe N 88 W 214.80'



Bearings are compass bearings, corrected for declination, all distances are to a double-headed nail in the side of the witness object unless otherwise noted.

Signed by Neil E Hill P.S.

Date 12-29-98

Surveyor's Michigan License No. 27447