

1994 Mackinac County Remonumentation Corner

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac

SURVEY &
REMONUMENTATION
APR 10 1995
COMMISSION

located in:

Corner Code --

1. Public Land Survey 42N R 4W
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

A-8

RECEIVED & FILED
DIANE BRANKOVICH
MACKINAC COUNTY REGISTER OF DEEDS

NOV 09 1994
AM PM
7/8/9/10/11/12/1/2/3/4/5/6

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, David B. Guthrie in a field survey on July 21, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1840: Established by Wm. Burt G.L.O Survey. Set a wood post and
referenced:
Spruce 6/S10W/60
Cedar 6/N60W/58

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994: Found 3/4" Iron Pipe at the intersection of trails West and South.
(Source unknown)

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 8-16-94

James H. Granga

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1994: Set Mackinac County Remonumentation Corner.
A 5/8" by 24" Iron Rod with a 3" aluminum cap stamped to identify,
set 6" below the road gravel surface.

Referenced:
S17°W - 64.40 feet - 6" Balm of Gilead
S53°W - 50.32 feet - 3" White Birch
S41°W - 52.45 feet - 8" Spruce
S79°W - 43.75 feet - 3" Balm of Gilead



Signed by David B. Guthrie

Date Oct. 21, 1994

Surveyor's Michigan License No. 22435