JAN 21 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 Mackinac County Remonumentation Corner

For corners in

Mackinac County Located in: Corner Code # M-1, 1. Public Land Survey **T43N R1W** T43N R1E A-1 (Same corners T44N R1E A-13 Chippewa T44N R₁W M-13 County) 2. Property Controlling Т S R S in Section Т R Miscellaneous S T R Property in Sec. S Т R ACCEPTED BY THE MACKINAC COUNTY RECEIVED & DIANE FRANKOVICH ACKIN ACCOUNTY PEGIST OF DEEDS

DEC 3 0 1998

PM71819110111112111213141516

Register of Deeds Stamp & File Number


Lot No. , Recorded Plat 5. Private Claims

SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER P.A. 345 OF 1990 AT A MEETING HELD ON

11-20-08

I, Keith R. Waters, in a field survey on November 11, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.



A. Description of original monument and accessories and/or subsequent restoration;

M-1 Corner Common to T43N, R1E & T43N, R1W & T44N, R1E, & T44N, R1W

1840 - Original corner established by William A. Burt.

1982 - LCRC, liber 5, page 229, Chippewa County corner records. W.L. Karr, P.S. 27450, found 5/8" iron in mon. box.

1991 - MDOT notes. Found corner and witnessed prior to road construction. Witnesses: Power Pole, N73°E 76.50' -Power Pole, N67°W 52.11' - Power Pole, S17°W 76.54' - Power Pole, S70°W 76.51'.

1992 - LCRC, liber 7, page 359, Chippewa County corner records. Neil E. Hill, P.S. 27447, found boat spike bent over in monument box. Reset corner with a 1/2" iron from 1991 witnesses. Witnesses: Wood Building Corner, S39°E 127.64' - P. Pole, N73°E 76.46' - P. Pole, N67°W 52.09' - P. Pole, S17°W 76.53' - Guy Pole, S70°W 76.52'.

1994 - LCRC, liber 8, page 307, Chippewa County corner records. Keith R. Waters, P.S. 33142, found 1/2" iron with cap #27447 in a monument box and all witness objects as called for in 1992 LCRC.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being perpetuated as part of the Mackinac County Remonumentation Program. Found a ½" iron with cap #27447 in a monument box and all witness objects as called for in 1994 LCRC.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found a ½" iron with cap #27447 in a monument box at the corner location, which falls in the approximate centerline intersection of Highway M-129 and Main Street in Pickford. Witnesses:

Wood Building Corner, S39°E 127.64'

Nail and MDOT reference tag in side of Power Pole, N73°E 76.46'

Nail and MDOT reference tag in side of Power Pole, N67°W 52.09'

Nail and MDOT reference tag in side of Power Pole, S17°W 76.53' Nail and MDOT reference tag in side of Guy Pole, S70°W 76.52'



Signed by Keith R. Wal

15-53-98 Date

Surveyor's Michigan License No. 33142

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983 REVISED OCT., 1995