

1993

1993 Mackinac County Remonumentation Corner

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac

(County)

Located In:

Corner Code #

1. Public Land Survey

T 43N R 2W

E-4

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

RECEIVED & FILED
DIANE ERIK EDVICH
MACKINAC COUNTY CLERK OF DEEDS

OCT 23 1993

AM PM
7/8/9/10/11/12/1/2/3/4/5/6

Register of Deeds Stamp & File Number

I, David B. Guthrie, in a field survey on June 23, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845: Established by J.H. Mullett, G.L.O. Survey

Set a wood post and referenced: 4"Cedar-S31°E-15Lks./4"birch-N44°W-10Lks.

1971: Survey by C. Eugene Ostling.

1971: Survey by Mary C. Feindt.

1987: Survey by Richard L. Hays of Nordlund & Assoc. for U.S. Forest Service.
1989

NOTE: Corners as set by Ostling and Feindt were not accepted by Hays and the U.S. Forest Service.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1993: Found a 2½" x 3' aluminum monument with a 3" aluminum cap stamped to identify the corner. The corner was set in 1989 by Richard L. Hays, P.S. No. 25847, by single proportionate measurement between the Northwest and Southwest corners of Section 9. The corner was recorded on March 20, 1990. (Book D, page 18)

Plat of Survey Recorded as U.S. Gov't. Plat of Survey No. 14.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1993: N09°W - 37.67 feet - (R=37.64') - 8" Maple

N20°E - 28.00 feet - 10" Birch

S59°W - 50.90 feet - 18" Cedar

S22°E - 70.16 feet - 23" Spruce

North - 1.50 feet - Steel Post

S18°E - 76.60 feet - ½" iron rod placed by C. Eugene Ostling.

(Tree references are blazed and tagged)

The monument is a 2½"x3' aluminum monument with a 3" aluminum cap stamped to identify the corner.

Signed by David B. Guthrie Date 9/23/93

Surveyor's Michigan License No. 22435



D-0197