

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970
MACKINAC CO. 4 CORNERS

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>44</u> N. <u>SE</u> R. <u>7</u> IX <u>W.</u>		<u>K-7, K-8, L-7</u>
2. PROPERTY CONTROLLING IN SECTION <u>24</u> T. <u>44</u> N. <u>SE</u> R. <u>7</u> IX <u>W.</u>		<u>10</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ S. _____ R. _____ E. _____ W. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Gerald L. Wiggins, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6-16, 1987, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- K-7 N.W. Section Corner of Section 24. OBT'S: Spruce 10, N28°W, 14 lks. & Spruce 7, N11°W, 14 lks.
- K-8 West 1/4 Corner of Section 24. OBT'S: B. Ash 10, N70°E, 26 lks. & B. Ash 12, S41°E, 37 lks.
- L-7 North 1/4 Corner of Section 24. OBT'S: Beech 8, S57°E, 26 lks. & Beech 8, N8°W, 31 lks.
- 10 South 1/16 Corner on West side of Section 24. Not previously set.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- K-7 Corner set by double proportionate measure between 1/4 corner 1/2 mile west, section corner 1 mile east, 1/4 corner 1/2 mile North, and section corner 1 mile south. Measurement west to stream fits original.
- K-8 Corner set M.P.O.L. between N.W. corner and S.W. corner of Section 24.
- L-7 Corner set by single proportionate measure between N.W. Corner and N.E. Corner of Section 24.
- 10 Corner set M.P.O.L. between West 1/4 Corner and S.W. Corner of Section 24.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

DNR Monuments set at all four corners.

- K-7 10" Cedar, N70°E, 7.8' & 8" Cedar, N5°E, 6.1' & 6" Cedar, N75°W, 11.4' & 4" Cedar, S11°W, 2.4'
- K-8 10" Cedar, S55°E, 15.3' & 10" Cedar, N23°W, 12.8' & 8" Cedar, N66°W, 22.2' & 8" Cedar, S88°W, 20.9'.
- L-7 12" Maple, S84°E, 13.7' & 6" Maple, N32°E, 14.4' & 4" Beech, N28°W, 11.7' & 10" Maple, S52°W, 10.7'
- 10 6" Twin Maple, S78°E, 20.5' & 10" Beech, N55°E, 14.2' & 6" Maple, N20°E, 20.0' & 10" Twin Maple, N86°W, 4.9' & Center Line of Road, South, 28.8'.

SIGNED BY

Gerald L. Wiggins
Gerald L. Wiggins

DATE 9-21-87

SURVEYOR'S MICHIGAN REGISTRATION NO.

23521

FOR STATE AND UNITED STATES AGENCIES:

