

B997883

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC 22 AM 9: 05

CARMELLA SABAUGH
 REGISTER OF DEEDS
 MACOMB COUNTY, MI

For corners in

MACOMB

(County)

Located In:

Corner Code #

CLINTON TWP.

1. Public Land Survey

T 2N R 13EC-1

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

Seg. #1 perLIBER **06161PG239**

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	13		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, BRUCE ANTCLIFF, in a field survey on NOVEMBER 29, 19 93,
 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
 in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
 current manual of survey instructions of the United States Department of the Interior, Bureau of Land
 Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
 Court of Law; established, re-established, monumented, re-monumented, recovered, found as
 expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
 on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

GLO-Post, NO WITS. REMAIN

MCRC (1934)-CROSS IN PAVT

SPIKE IN DE POLE, SW, 56.50'

SPIKE IN DE POLE, SE, 38.05'

SPIKE IN DE POLE, NW, 37.3'

SPIKE IN TEL POLE, N'LY, 23.4'

MDOT (1971)-1" PIN IN MON BOX

GUY POLE, S25E, 67.26'

PP, S32W, 66.91'

TEL POLE, N62W, 59.12'

GUY POLE, N45E, 26.42'

LCRC (1987) L4113, P178-IRON IN MON BOX

CENTER OF GATE WELL, NE, 53.35'

CENTER OF GATE WELL, NW, 52.10'

N&T #20623 SE FACE PP, SW, 66.82'

CENTER OF STORM MH, SE, 53.75'

MDOT (1988)-1/2" ROD IN MON BOX

MDOT N&T IN PP, S45W, 71.95'

MDOT N&T IN TEL POLE, N55W, 63.28'

MDOT N&T IN GUY/LIGHT POLE, N55E, 40.81'

MDOT N&T IN PP, S50E, 122.21'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" ROD/MON BOX

NO PREVIOUS WITNESSES REMAIN.

VERIFIED MDOT DISTANCE TO C-13, T3N, R13E (R=594.85', M=594.89')

VERIFIED MDOT DISTANCE TO D-13, T3N, R13E (R=2080.13', M=2080.17')

VERIFIED MDOT DISTANCE TO C-2, T2N, R13E (R=2672.90', M=2672.89')

C. Description of monument for corner and accessories established to perpetuate locating the position of

SET MACOMB COUNTY REMONUMENTATION MARKER AND CAP #25826 IN EXIST. MON. BOX.
 WITNESSES

C.L. STORM MH, S28E, 91.14'

SET NAIL & MC TAG SW FACE PP, S40E, 96.14'

SET NAIL & MC TAG SE FACE PP, S60W, 63.78'

SET "+" TOP CURB N SIDE M-59, N40W, 40.89'

SET NAIL & MC TAG SE FACE PP, N60E, 41.06'

The selected location is accepted by me and is generally accepted by Professional Surveyors as
 the best available evidence of the position of the original corner.

Signed by Bruce AntcliffDate 12-9-93Surveyor's Michigan License No. 25826

ACCEPTED BY THE MACOMB COUNTY
 SURVEY PEER GROUP AS THE OFFICIAL
 CORNER UNDER MICHIGAN PUBLIC ACT 345
 OF 1990 AT A MEETING HELD ON
12-1-93
Frank J. Decker
 FRANK J. DECKER, P.S., PE, CHAIRMAN

