

SURVEY &  
REMONUMENTATION

APR 28 1995

LAND CORNER RECORDATION CERTIFICATE  
COMMISSION Filing Requirement of Act 74, Mich. P.A. 1970

C152224

For corners in

MACOMB

(County)

Located In: Clinton  
Township

Corner Code #

1. Public Land Survey

T 2N R 13E

D-7

2. Property Controlling  
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

94 DEC 14 AM 10:52

REGISTERED  
DEEDS  
CL. MT

LIBER 6527 PAGE 801

Register of Deeds Stamp & File Number

I, Randy Kolehhouse, in a field survey on July 26, 19 94,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

| D-7 | 1817 | G.L.O.       | Notes                | Preston   | NA     | Post           |
|-----|------|--------------|----------------------|-----------|--------|----------------|
|     | 1976 | Cert. Survey | L. 2714 P's. 460-465 | Dely      | #5234  | 1/2" Iron Pipe |
|     | 1980 | L.C.R.C.     | L. 3350 P. 762       | Smith     | #16052 | Iron           |
|     | 1986 | L.C.R.C.     | L. 4072 P. 920       | Soderberg | #17635 | Rerod          |

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-7 Found 1/2" Iron Pipe at N. edge of pavement of 17 Mile Road.

L.C.R.C. L. 3350 P. 762

Top Nut of Hyd. S 80° W 66.35'

Top Nut of Hyd. WSW 66.17'

SW Cor. Cemetery Fence N 61.15'

Gate Valve and Well ESE 128.26'

Survey L. 2714 P. 460

Top of Hyd. S 80° W 66.21'

Measure W 2681.55 to C-7 (G.L.O. 2640)

Measure E 2846.68 to E-7 (G.L.O. No Dist. Given)

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER  
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN  
PUBLIC ACT 345 OF 1990 AT A MEETING HELD  
ON 9-20-94

William E. Soderberg  
WILLIAM E. SODERBERG, P.S., CHAIRMAN

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-7 I replaced the found 1/2" Iron Pipe with a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County  
Monument MI Act 345 #25854," also set Monument Box.

PK W Face Util. Pole N 06° E 64.20'

Center Line GV&W S 70° E 128.10'

Center Line Top Nut Hyd. S 72° W 66.21'

Set PK & Remon. Washer N 33° W 33.70'

The selected location is accepted by me and is generally accepted by professional surveyors as the best  
available evidence of the position of the original corner.

Signed by Randy J. Kolehhouse

Date 10/14/94

25854

Surveyor's Michigan License No.

