

SURVEY &
REMONUMENTATION

C0158350 LIBER:06543 PAGE:372 08:35A 01/05/1995
APR 28 1995 CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in:

MACOMB (County) Located In: CLINTON Corner Code # D-11
1. Public Land Survey T 2N R 13E
2. Property Controlling in Section S T R
3. Miscellaneous Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 and a central dot at row 11, column D.

I, STEVEN E. DUNN, in a field survey on DECEMBER 12, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
GLO POST - NO EVIDENCE OF ORIGINAL CORNER FOUND
GLO ORIGINAL SURVEY PERFORMED BY PRESTON 8-18-1818

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 12-13-94
WILLIAM E. SODERBERG, P.S., CHAIRMAN

L.C.R.C. NAME AND NUMBER DESCRIPTION
L. 3004 P. 130 WILLIAM J. COULTER, #14760 FOUND 1/2" STEEL ROD

DATE
SEPTEMBER 19, 1978

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-11 1/4 CORNER

FOUND ALUMINUM TAG WITH "SURVEY MARK" STAMPED ON TAG ON "T" IRON IN ASPHALT PAVEMENT. VERIFIED LOCATION BY COMPARING FOUND WITNESS TIE FROM L.C.R.C. AND THE DISTANCE FROM D-11 TO E-11 AS SHOWN ON "BENNETT INDUSTRIAL COMPLEX SUBDIVISION" AS RECORDED IN LIBER 91 OF PLATS ON PAGES 32-33 (M.C.R.).

FOUND WITNESSES
L. 3004 P. 130 SOUTH 51.95' PK IN DETROIT EDISON POLE

FIELD MEASUREMENTS AND RECORDED DISTANCES
D-11 TO C-11 2698.73' (M.) 39.95 (GLO) 2636.70'
D-11 TO E-11 2715.95' (M.) 2716.39' (RECORD FROM PLAT) 39.95 (GLO) 2636.70'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
D-11 T.2N., R.13E. 1 REPLACED ALUMINUM TAG WITH 3/4" x 24" IRON ROD WITH 2" DIAMETER ALUMINUM CAP STAMPED "MACOMB COUNTY MONUMENT MI. ACT 345 #28408" IN A NEW MONUMENT BOX.
WITNESSES
S.07°W. 52.04' FOUND PK NAIL IN WEST FACE OF UTILITY POLE
N.04°E. 99.35' FOUND PK NAIL IN EAST FACE OF UTILITY POLE
N.58°W. 78.76' FOUND PK NAIL IN NORTHEAST FACE OF LIGHT POLE
N.80°E. 154.44' CENTER TOP NUT ON FIRE HYDRANT
SOUTH 104.50' CENTER TOP NUT ON FIRE HYDRANT
THE SELECTED LOCATION IS ACCEPTED BY ME AND IS GENERALLY ACCEPTED BY PROFESSIONAL SURVEYORS AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Steven E. Dunn Date Dec 20, 1994
Surveyor's Michigan License No. 28408

