

SURVEY &
REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

APR 07 1998

For corners in

Macomb (County)	Located In: Washington Township	Corner Code #
1. Public Land Survey	T <u>4N</u> R <u>12E</u>	<u>B-1</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

SECTION

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Huston K. Kennedy, in a field survey on 4/17, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

1817-GLO Wampler, D.S.; No post was set

- 1.) 1977-Kobs, PS #14097; LCRC L.2765, Pg.543 - Fnd "T" Iron
- 2.) 1976-Kobs, PS #14097; Survey L.2765, Pg.536 - Fnd "T" Iron, used same wit as 1977 LCRC
- 3.) 1976-Kobs, PS #14097; Survey L.2765, Pg.538 - Fnd "T" Iron, used same wit as 1977 LCRC
- 4.) 1978-Kobs, PS #14097; Survey L.3047, Pg.894 - Fnd "T" Iron, used same wit as 1977 LCRC

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1997 Kennedy Surveying, Inc. - Kennedy, PS #17623 - The corner has been perpetuated with a "T" Iron 2 feet South of the existin centerline of 32 Mile Road extending to the East & West, which has a bituminous surface, and 12 feet West of driveway for hou #2920. The corner as recovered is 3.20 feet South of the township line. I found a 3/4" Iron Rod 101.74 feet to the West, whi is being used and accepted as the South 1/4 corner of Section 31, T5N, R12E, Bruce Twp., (B-13).

See back side of LCRC for Field Measurements

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN
PUBLIC ACT 345 OF 1990 AT A MEETING HELD
ON JULY 10, 1997
William E. Soderberg
WILLIAM E. SODERBERG, P.S., CHAIRMAN

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-1 I set a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345" #17623 in a new Monument E on the township line
S21°W 53.16' Set PK & Remon Washer West face 21" White Pine
N18°W 113.30' Set PK & Remon Washer West face 23" Pine
N33°E 170.26' Set PK & Remon Washer NW face Power Pole
S66°E 92.24' Set PK & Remon Washer NE face 12" Ash
West 101.74 feet South 1/4 corner of Section 31, T5N, R12E, Bruce Twp., (B-13)

South 3.20 feet from

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by [Signature]
Surveyor's Michigan License No. 17623

Date 8-11-97



768

FIELD MEASUREMENTS BETWEEN

B-1 to A-1

No GLO
Survey dated 12/78, L.3047, Pg.894 = 2737.96 Ft.
GRID-MEA = 2737.89 Ft.
EDM-MEA = 2738.20 Ft.

B-1 to B-13

No GLO
GROUND-MEA = 101.74 Ft. (mea.)

B-1 to C-1

No GLO
Survey dated 8/76, L.2765, Pg.538 = 2678.71 Ft.
Survey dated 7/76, L.2765, Pg.536 = 2678.71 Ft.
GRID-MEA = 2678.68 Ft.