

**SURVEY &
REMONUMENTATION**

C152199

APR 28 1995

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

corners in **COMMISSION**
Macomb
(County)

Washington
Located In: Twp. Corner Code #

LIBER **6527** PAGE **776**

94 DEC 14 AM 10:50

CAPM BAUGH
REG. OF DEEDS
MACOMB COUNTY, MI

Register of Deeds Stamp & File Number

Public Land Survey	T <u>4N</u> R <u>12E</u>	<u>T-6</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
Property Controlling	S _____ T _____ R _____	_____
in Section	S _____ T _____ R _____	_____
Miscellaneous	S _____ T _____ R _____	_____
Property in Sec.	S _____ T _____ R _____	_____

Lot No. _____, Recorded Plat _____
Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Huston K. Kennedy in a field survey on September 10, 1994, hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the recent manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as recorded below:

TE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

- 7-GLO Wampler, D.S.; Set Post; 18" White Oak S42°W 17 Links; 16" White Oak N76°E 24 Links
- 1979-Coulter, P.S. #14760; LCRC L.3126, Pg.367 - Fnd P.K. Nail
- 1984-Kobs, P.S. #14097; LCRC L.3705, Pg.145 - Fnd P.K. Nail
- 1979-Dunn, P.S. #5557; Survey L.3084, Pg.709 - Set P.K. Nail from previous survey L.2420, Pg.319
- 1984-Kobs, P.S. #14097; Survey L.3705, Pg.116 - Fnd P.K. Nail

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 4 Kennedy Surveying, Inc. - Kennedy, P.S. #17623 - Fnd PK Nail in the centerline of Van Dyke Road, which has a bituminous surface, and 20' South of Klarney Road, extending to the West with a fence row extending to the West, and a tree-fence row extending to the East.

Witnesses from LCRC #2 and Survey #3 were used to recover and verify the location of the found PK Nail.

FIELD MEASUREMENT BETWEEN

I-6 to I-5 2761.82 Feet
I-6 to I-7 2638.98 Feet

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 9-20-94

William E. Soderberg
WILLIAM E. SODERBERG, P.S., CHAIRMAN



Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- I replaced the PK Nail with a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345 #17623" in a new Monument Box.
- N40°W 57.48' Set PK & Remon. Washer NE face Power Pole
- N82°E 32.92' Set PK & Remon. Washer South face Power Pole
- S22°E 124.75' Set PK & Remon. Washer SW face Power Pole
- S80°W 39.98' Set PK & Remon. Washer South face Guide Pole

selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the location of the original corner.

Recorded by [Signature] Date September 20, 1994
Surveyor's Michigan License No. 17623