

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Macomb
 (County)

Washington Twp.

Located In: Corner Code #

1. Public Land Survey	T <u>4</u> N	R <u>12</u> E	<u>M-4</u>
	T _____	R _____	_____
	T _____	R _____	_____
	T _____	R _____	_____
2. Property Controlling in Section	S _____	T _____	R _____
	S _____	T _____	R _____
3. Miscellaneous Property in Sec.	S _____	T _____	R _____
	S _____	T _____	R _____

SURVEY & REMONUMENTATION

FEB 27 1997

COMMISSION

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Huston K. Kennedy, in a field survey on April 12, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		16		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

1817-GLO Wampler, D.S.; Set Post 11" Beech N27°W 7 Links; 5" Elm N47°E 21 Links
 1.) 1980-Kobs, PS #14097; LCRC L.3287, Pg.579 - Fnd 1/2" Iron Bar at Anchor Post

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 4-16-96

William E. Soderberg
 WILLIAM E. SODERBERG, P.S., CHAIRMAN

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1996 Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd 1/2" Iron Rod 2" above the surface at the base of old 3-way fence corner. A fence tree line extending to the North, South & West. The West 1/4 corner of Section 7, T4N, R13E, Ray Twp., (A-4) is located 58.98 feet to the South.

Witnesses from LCRC #1 were used to recover and verify the location of the found 1/2" Iron Rod.

Field Measurements see back side of LCRC C0458179 LIBER:07298 PAGE:208 10:47A 01/02/1997
 CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-4 I replaced the found 1/2" Iron Rod with a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345" #17623
 S63°E 168.80' Set PK & Remon Washer North face 10" Ash
 Due North 67.17' Set PK & Remon Washer East face 9" Ash
 Due South 139.92' Set PK & Remon Washer East face 19" Ash
 S32°W 12.42' Set PK & Remon Washer NW face 3" Ash
 South 58.98 feet West 1/4 corner Section 7, T4N, R13E, Ray Twp., (A-4)

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by [Signature]
 Surveyor's Michigan License No. 17623

Date 12-6-96



29

588

FIELD MEASUREMENTS BETWEEN

M-4 to A-4 58.98 Ft. L.3880, Pg.84, no GLO
M-4 to M-3 GLO = 40 chains or 2640.00 Ft.
M-4 to M-3 2712.00 Ft. L.3880, Pg.84, 2712.58 Ft. (GPS-MEA)
M-4 to M-5 GLO = 40 chains or 2640.00 Ft.
M-4 to M-5 2693.29 Ft. (GPS-MEA)

C0458179 LIBER:07298 PAGE:209 10:47A 01/02/1997
CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

SURVEY &
REMONUMENTATION

FEB 27 1997

COMMISSION