

SURVEY &
REMONUMENTATION

APR 29 1996

COMMISSION

C0212001 LIBER:06663 PAGE:858 12:21P 06/06/1995
CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Macomb

(County)

Located In: Washington
Twp.

Corner Code #

1. Public Land Survey

T 4N R 12E

M-5

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Section

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Huston K. Kennedy, in a field survey on April 28, 19 95,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and
5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found
as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

1817-GLO Wampler, D.S.; Set Post 14" Ash N20°E 20 Links; 16" Black Oak N30°W 20 Links

1.) 1979-Kobs, PS #14097; LCRC L.3162, Pg.603 - Fnd 1/2" Iron Bar

2.) 1979-McMahon, PS #4018; Survey L.3106, Pg.514 - Set Iron, no witnesses

3.) 1979-Kobs, PS #14097; Survey L.3162, Pg.609 - Fnd 1/2" Iron Bar, used same wit as 1979 LCRC

4.) 1988-Kobs, PS #14097; Survey L.4021, Pg.514 - Fnd 1/2" Iron Bar, used same wit as 1979 LCRC

5.) 11993-King, PS #30085; Survey L.5831, Pg.260 - Fnd 1/2" Iron Bar, used same wit as 1979 LCRC

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1995 Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd 1/2" Iron Rod w/cap #14097 2" above surface and 78.50 feet North of the
centerline of 30 Mile Road extending to the East & West, which has a gravel surface and a tree-rock row extending to the North
& South. The corner common to Section 7 & 18, T4N, R13E, Ray Township (A-5) is located 76.29 feet to the South.

Witnesses from LCRC #1 were used to recover and verify the location of the found 1/2" Iron Rod w/cap #14097.

FIELD MEASUREMENTS BETWEEN

M-5 to L-5 2634.58 Ft., GLO = 39.72 chains or 2621.52 Ft.

M-5 to M-6 2721.64 Ft., GLO = 40.00 chains or 2640.00 Ft.

M-5 to A-5 (Ray Twp.) 76.29 Ft. to the South, GLO = 1.11 chains or 73.26 Ft.

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN
PUBLIC ACT 345 OF 1990 AT A MEETING HELD
ON 5-23-95

William E. Soderberg
WILLIAM E. SODERBERG, P.S., CHAIRMAN

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-5 I replaced the found 1/2" Iron Rod with a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act
345 #17623"

S03°E 16.36' Set PK & Remon. Washer East face Power Pole

Due South 38.00' Set PK & Remon. Washer East face 21" Elm

S22°E 54.83' Set PK & Remon. Washer SW face 27" clump Ash

S35°E 57.83' Set PK & Remon. Washer SW face 11" Ash

South 76.29 Ft. corner common to Sections 7 & 18, T4N, R13E, Ray Township.

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the
position of the original corner.

Signed by

Date May 30, 1995

Surveyor's Michigan License No.

17623

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 14, 1975
REVISED JAN., 1983

