

DEC 09 1999

SECTION LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Manistee County (County) Located In: Corner Code #
M-05 MC
1. Public Land Survey T 21N R 17W Meander Cor.
T R West of SE.
T R Sec. Cor. of
T R Section 12
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

REGISTER'S OFFICE
MANISTEE COUNTY

99-317 at 11:15AM
SEP 23 1999

Register of Deeds Stamp & File
Number

I, Anthony M. Slawinski, in a field survey on August, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
M-05 MC Meander Corner West of Southeast Sec. Cor. Sec. 12, T21N, R17W

Set by John Brink in 1839

- W. Oak 28" in dia. S 55° W 20 links (13.2') (Gone)
- W. Pine 14" in dia. N 63° W 82 links (54.12') (Gone)

Field Notes by Slawinski (1962)
Used to establish Section line only
No witnesses

Survey Cert. by Slawinski 1991
Used to establish Section line only
No Witnesses

Field Notes by Slawinski (1969)
Used to establish Section line only
No witnesses

Field Notes by Abonmarche 1999
Used to establish Section line only
No witnesses

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
M-05 MC Meander Corner West of Southeast Sec. Cor. Sec. 12, T21N, R17W

On August 19, 1999, I, Anthony Slawinski, along with a field crew from Abonmarche used 3 previous surveys that I made to establish the South line of Section 12, T21N, R17W. Then we went government measure (2475.00') East along the established South Section Line from the South 1/4 Corner and set the Meander Corner West of the Southeast Section Corner of Section 12, T21N, R17W. The Southeast Section Corner of Section 12, T21N, R17W is in Manistee Lake. I found no evidence to dispute the location of this corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
M-05 MC Meander Corner West of Southeast Sec. Cor. Sec. 12, T21N, R17W

On August 19, 1999 I set a Manistee County Monument in the location established in part B as a careful and faithful re-establishment of the position of the original corner, and witnessed by:

- S 81° E 133.51' End fence post, measured to the face of it
- S 21° W 88.55' 4" Monitor Well, measured to the face of it
- N 68° W 126.01' Corner Fence Post, measured to the face of it
- N 52° W 91.58' East Gate Post, measured to the face of it

Note: Meander Corner is ±147' West of Manistee Lake (Area has been filled extensively over the years)

Note: Meander Corner is 2475.00' East of the South 1/4 Corner of Section 12 T21N, R17W.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5			4		3		2		1
3													
4	7			8			9		10		11		12
5													
6	18			17			16		15		14		13
7													
8	19			20			21		22		23		24
9													
10	30			29			28		27		26		25
11													
12	31			32			33		34		35		36
13													

Signed by Anthony M. Slawinski
Surveyor's Michigan License No. 13597



Date 9-7-99

Corner 14 - 05 MC
I, Anthony M. Slawinski,
Surveyor, do hereby certify that the above
survey was made in accordance with the
Michigan Survey and Monument Act, MCL 54.261
et seq. Date of Peer Review: SEP 17 1999