LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of A	ct 74, Mich. P.A.	1970		·	भूत ^त	
For corners in			1	REGISTER'S OF	FICE	
Manistee Local (County)	ated In:	Corner Cod	e#	MANISTEE COL	£191.000	
T T T_ <u>2</u> :	2N R 17W R R R R 2N R 16W	M-12 East ¼ Cor. Sec. 36 A-12		JUN 2 9 199 REGISTER OF D	K	
2. Property Controlling ST in Section ST 3. Miscellaneous ST Property in Sec. ST 4. Lot No, Recorded Plat 5. Private Claims	R R R	West ¼ Cor. Sec. 31		Register of Deeds Stamp & File Number		
I, Anthony M. Slawinski, in a field surunder requirements of P.A. 74, Michigan P.A. of above were in conformance with regulations and survey instructions of the United States Departs by a decree of a Court of Law and /or that the were in conformance with the rules of the Mic Court of Law; established, re-established, monuted NOTE: Not more than 2 corners, all in the on this certificate.	f 1970, the corner po d rules therefore as re- ment of the Interior, l e corner points menti- higan Board of Land mented, recovered, fo	pints mentioned in equired in the curr Bureau of Land M oned in lines 3, 4 Surveyors or by bund as expressed	lines 1 and 2 ent manual of anagement or and 5 above a Decree of a below:	A B C D E F G R 1		
A. Description of original monument and	accessories and/or	subsequent rest	oration:	8 -19 -20 -21 -22	- 23- 24	
Set by John Brink 1837 1. Black Oak 9" N 41° W 36 links 2. White Pine 18" S 20° W 62 links B. Description of corner evidence found a reestablishing corner;	(Gone) (Gone) and/or method app	lied in restoring	or	1 30 29 28 27 1 31 32 33 34	26 25	
Information Referenced:						
Oakfield Subdivision (8-6-1881) Liber 2, Page 26	U.S31 Right	, .				
Sibley's Addition to the Village of Parkdale (4-3-30) Liber 4, Pages 4&5 Ager Subdivision (7-11-57) Liber 4, Page 31	3. NW 35.1 4. SWW 38 5. NE 47.79		(Gone) (Good) (Gone) (Gone)		County Peer Group P.A. 345 of 1990, It Act, MCL 54.261	
Field Notes by Abonmarche (1998)	Survey Certif	icate by Ross (1	995)		Coun P.A.	
On March 20, 1998, I, Anthony Slawinski, center line of Hill Road.	, Along with Abonn	narche, Found a	spike in the a	pproximate	Manistee Jant to nonume	
C. Description of monument for corner and	d accessories estab	olished to perpet	uate locating t	he position of the corner:	/ the t	
On June 10, 1998, I installed a Manistee (County Monument, re-establishment of	within a monun the location of	nent box, in th the original co	e exact location of the above mer, and witnessed by:	ratified by the Manistee County Peel plan adopted pursuant to P.A. 345 of late Survey and Remonument Act, MCL view:	
4. S 82° W 38.56′ 18″ Twin Maple, 60I 7. S 48° E 36.00′ Power Pole, 60D spik 8. S 30° W 8868′ 18″ White Oak, 60D 9. S 58° W 43.63′ 12″ White Pine, 60D	e in the South side spike in the East si	de			county gethe Si	
Note: South 1321 84 feet to the South 1/	16th Corner on the	Feet Section Lin	a of Section 3	6 T22N 917M	E (Sein E	

Corner is ±1100' North from the center line of Highway U.S. - 31.

YHOHTHA M. SLAWINSKI SURVEYOR NO. 13597

Surveyor's Michigan License No. 13597