

DEC 09 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Manistee (County) Located In: Corner Code #

1. Public Land Survey T 22N R 17W M-09 MC
 T R Witness to
 T R Meander Cor.
 T R N. of SE Cor.
 of Sec 24

2. Property Controlling S T ~~22N R 17W~~
 in Section S T R
 3. Miscellaneous S T R
 Property in Sec. S T R #003

4. Lot No. , Recorded Plat

5. Private Claims

REGISTER'S OFFICE
MANISTEE COUNTY

99-221 at 1:15pm

JUL 22 1999

Barbrah Six

REGISTER OF DEEDS

Register of Deeds Stamp & File
Number

I, Anthony M. Slawinski, in a field survey on June 7, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
 M-09MC Witness Corner to Meander Corner North of Southeast Section Corner Section 24, T22N, R17W

Set by John Brink in 1837 by going north from the Southeast Sec. Corner of Section 24 10.00 (chains) Int S Margin of Lake - Set Post

1. B. Ash 8" dia. S 8½° W 1.85 links (1.22') (Gone)

Survey Certificate by Martin 1945 (No witnesses)

Survey Map by Bruning 1977 (No witnesses)

Field Notes by Abonmarche 1999

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 M-09MC Witness Corner to Meander Corner North of Southeast Section Corner Section 24, T22N, R17W

On June 7, 1999, I Anthony Slawinski, with a crew from Abonmarche, used the line established by Martin in 1945 to project North along the East Section Line to the edge of a swamp. We set a Witness Corner here, as the original corner now falls within Bar Lake. The new Witness Corner is ±190' south of the shore of Bar Lake. The corner was set this far from the lake in order that a tripod be able to be set up over the point. Going any further North would have made that impossible. I found no other evidence to dispute the location of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
 M-09MC Witness Corner to Meander Corner North of Southeast Section Corner Section 24, T22N, R17W

On June 7, 1999, I set a Manistee County monument 417.14 feet North of the Southeast Section Corner of said section as the best available location to set the witness corner to the meander corner. The witness corner is 242.86' South of the position of the original meander corner. Witnessed by:

2. S 71° W 6.02' 8" Ash set 60d on North side of tree
3. N 23° W 15.96' 6" Ash set 60d on West side of tree
4. S 45° E 30.20' 8" Ash set 60d on West side of tree
5. S 11° E 29.80' 8" Ash set 60d on West side of tree

Note: Corner is ±190' South of the Shore of Bar Lake.

Note: Corner was set ±3" above grade.

Corner M-09MC ratified by the Manistee County Peer Group according to the county plan adopted pursuant to P.A. 345 of 1990, as amended, (being the State Survey and Remonument Act, MCL 54.261 et seq.). Date of Peer Review: Anthony M. Slawinski

JUL 6 1999



Signed by

Anthony M. SlawinskiSurveyor's Michigan License No. 13597

Date

7-2-99