

Land Corner Recordation Certificate
Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Craig W. McVean Field Survey Date: Oct. 24, 2016
For corner(s) in: Manistee County

Original Public Land Survey Corner Corner Code
S T R
S T R
S T R
S T R

Property Controlling Corner Corner Code
S T R
S T R
S T R
S T R

Property Corner Corner Code
S 1 T 23N R 13W 5
S T R
S T R
S T R

Protracted Public Land Survey Corner Corner Code
S 1 T 23N R 13W L2
S T R
S T R
S T R

Table with 13 rows and 13 columns (A-M). Contains section numbers 1-36 and a circled '1' in row 2, column L.

Part A: Corner History

L2 - C 1/4 Sec. 1, T23N, R13W
- None

5 - CN 1/16 Corner Sec. 1, T23N, R13W
- None

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

L2 – C ¼ Corner Sec. 1, T23N, R13W – Set
2" Aluminum Cap on 5/8" x 34" rebar per Standard
BLM procedure.
Old E-W fence in trees is North 18'±

5 – CN 1/16 Corner Sec. 1, T23N, R13W – Set
2" Aluminum Cap on 5/8" x 34" rebar per Standard
BLM procedure. Old N-S barbwire on ground is
4'± West.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

L2 – C ¼ Corner Sec. 1, T23N, R13W –
Stamped 2" Aluminum Cap on 5/8" x 34" long iron
rebar.
Set Blue Composite Post with loc. tag 1' SW
North 16.58' to set N & T in W. side 12" S. Maple
S63°E 14.17' to set N & T in N. side 6" S. Maple
S03°W 24.82' to set N & T in W. side 10" Cherry
S79°W 45.98' to set N & TY in S. side twin 18" &
10" S. Maple

5 – CN 1/16 Corner Sec. 1, T23N, R13W – Stamped
2" Aluminum Cap on 5/8" x 34" long iron rebar.
S31°W 7.65' to set N & T in E. side 9" S. Maple
S52°E 10.53' to set N & T in NE side 22" S. Maple
S87°W 47.27' to set N & Y T in N. side 11" R. Pine
N41°W 72.50' to set N & T in NE side 8" R. Pine



Craig W. McVean

Craig W. McVean

1/25/2017
Date

Professional Surveyor's License No.: 39088

Prepared By:
Craig W. McVean
Michigan Dept. of Natural Resources
8015 Mackinaw Trail
Cadillac, Michigan 49601